

## Contar Anti Slip Area Marking System



### Description

The Contar AS AM has been designed to deliver exceptional slip and skid resistance to any pedestrian and vehicular area. Using methyl methacrylate resin it is cold applied that offers outstanding durability, flexibility and resistance to extreme operating conditions. Contar AS AM is suitable for external use onto both concrete and asphalt substrates.

### System Features & Benefits

- **Rapid installation, minimal disruption**  
*Full cure time under 1 hour*
- **Outstanding durability**  
*Up to three times the life expectancy of traditional products.*
- **Cold applied**  
*No hot works, No big vehicles required and minimal environmental impact*
- **Highly resistant to UV light**  
*Durable and 'fit for purpose'*
- **Choice of finishes**  
*Colours and textures can be adjusted to suit*
- **Installation temperature range 0°C to +30°C**
- **Excellent chemical and road salt resistance**

### Installation Services

The installation should only be carried out by a Contar approved contractor with the documented quality assurance scheme. Contact Contar Resins Ltd for details.

### Fields of Application

- Cycle lanes
- Pedestrian routes
- Bus lanes
- Pedestrian crossings
- Highway area marking
- Anti skid surfacing
- Carparks

### Substrate Requirement

Substrate must be dry, free from laitance, dust and other contaminations. Check the relative humidity at ground level. Can be laid on both asphalt and concrete substrates. Contact Contar Resins Ltd for details and technical advice.

### Model Specification

**Product:** Contar AS AM

**Finish:** textured

**Overall thickness:** 2-3mm

**Colour:** as per Contar range

**Manufacturer:** Contar Resins Ltd

*(Preparatory work and application in accordance with the manufacturer's instructions)*

### System Overview

Contar Primer

Contar body-coat RTU

Contar Aggregate

Contar Sealer

### **Chemical resistance**

Excellent resistance to diesel, engine oils and road salts.  
Limited resistance to unleaded and super unleaded petrol.

### **Speed of cure**

Pot Life 15-20 mins\*

*\*Pot life & curing times will be dependent on substrate and air temperature.*

Finish curing to full specification-1 hour

*Materials can be stored unopened for up to 6 months in dry, cool conditions.  
**Caution**-Contar materials have a characteristic odour during application which is nontoxic and non-injurious to health. Ensure adequate ventilation is available. See material safety data sheet for full information or contact Contar technical dept.*

### **Mixing & Application**

Refer to Contar Resins Ltd installation guide

### **Standard Colours**

Black RAL 9011	White RAL 9010	Traffic Purple RAL 4006	Traffic Green RAL 6024
Traffic Yellow RAL 1023	Traffic Blue RAL 5017	Traffic Grey RAL 7043	Mid Grey RAL 7045
Traffic Red RAL 3020	Grass Green RAL 6010		

#### **Note:**

*Contar Resins Ltd endeavors to ensure that all information and advice given is accurate and correct. However, the company cannot take responsibility for the selection of products for specific applications. Therefore, any prospective customers should satisfy themselves that the product is suitable for the environment in which it will be installed. Accordingly, Contar cannot take responsibility for the selection of a product unsuitable for the application. The information detailed in this communication is liable to change without prior notification. All resin floors are hand applied resulting in a surface texture that can vary.*