

Contar Pothole Repair System



Description

Contar Pothole repair system has been designed and developed as a very fast curing pothole repair solution that is based on the high performing methyl methacrylate (MMA) resin. Contar Pothole Repair System is suitable for both concrete and asphalt substrates.

System Features & Benefits

- **System cures to full specification in 20 minutes**
Minimising disruption enabling rapid refurbishment
- **Strong bond to asphalt and concrete**
No need to prime, minimal preparation, outstanding longevity, no need to cut back (which makes the hole even bigger)
- **Exceptional chemical bond to both concrete and asphalt substrates and total impervious**
Exceptional durability and performance and will not suffer thaw / freeze damage or failure.
- **Easy to install**
Minimum tools required, no need to compact and available in kit form. Coverage 1m² @13mm
- **Installation temperature range 0°C to +30°C & excellent chemical and road salt resistance**

Installation Services

The installation should only be carried out by a Contar approved contractor with the documented quality assurance scheme. Contact Contar Resins Ltd for details.

Substrate Requirement

Substrate must be dry, free from laitance, dust and other contaminations. Check the relative humidity at ground level. Contact Contar Resins Ltd for details and technical advice.

Model Specification

Product: Contar Pothole Repair

Finish: Textured

Overall thickness: up to 300mm

Colour: Dark/black

Manufacturer: Contar Resins Ltd

(Preparatory work and application in accordance with the manufacturer's instructions)

System Overview

Contar Pothole repair resin

Contar Pothole aggregate

Contar hardener



Speed of cure

Pot Life 15-mins*

**Pot life & curing times will be dependent on substrate and air temperature.*

Finish curing to full specification-20 minutes

Materials can be stored unopened for up to 6 months in dry, cool conditions.

***Caution**-Contar materials have a characteristic odour during application which is nontoxic and non-injurious to health. Ensure adequate ventilation is available.*

See material safety data sheet for full information or contact Contar technical dept.

given is accurate and correct. However, the company cannot take responsibility for the selection of products for specific applications. Therefore, any prospective customers should satisfy themselves that the product is suitable for the environment in which it will be installed. Accordingly, Contar cannot take responsibility for the selection of a product unsuitable for the application. The information detailed in this communication is liable to change without prior notification. All resin floors are hand applied resulting in a surface texture that can vary. Colours may be different when installed on site due to substrate and installation methods.

Aftercare and Maintenance

The most efficient way of cleaning Contar systems would be to use a rotary scrubber dryer, with the facility to rinse and vacuum. To arrange a free demonstration please call our Technical Services Team.

Mixing & Application

Refer to Contar Resins Ltd installation guide

Before



After 15 minutes curing time

