

Contar Elastomeric Coving System



Description

Contar Elastomeric Coving System is made from technically advanced Urethane.

Fields of Application

Contar Elastomeric Cove system used in conjunction with Contar walkway MMA system for upstands and protrusions.

System Features & Benefits

- Permanently elastomeric
- Fibre reinforced for maximum film strength
- UV stable
- Hygienic and easy to clean
- Joint free
- Zero solvent odour

Substrate Requirement

Substrate must be dry, free from laitance, dust and other contaminations. Check the relative humidity at ground level and always use the correct Contar substrate primer prior to applying the Contar Coving System. Please contact Contar Resins technical team for further advice.

Tel: 01277843955

E-Mail: info@contarresins.co.uk

Model Specification

Product: Contar Elastomeric Cove System

Finish: Smooth

Colour: Grey

Preparatory work and application in accordance with the manufactures instructions.

Manufacturer: Contar Resins Ltd

System Overview

Contar Elastomeric FT base coat

Contar Elastomeric UV top coat

Installation Services

The installation should only be carried out by a Contar approved contractor. Obtain details of the Contar approved contractors by contacting Contar Resins Ltd or via our web site at

www.contarresins.co.uk

Chemical Resistance

Please contact Contar technical dept. for information.

Mixing & Application

Refer to Contar Resins Ltd installation guide

Speed of cure

Touch dry in 8* hours / hard dry in 24* hours

*Can accelerate

Aftercare and Maintenance

Clean regularly using a mop or cloth in conjunction with a mildly alkaline detergent

Note:

Contar Resins Ltd endeavors to ensure that all information and advice given is accurate and correct. However, the company cannot take responsibility for the selection of products for specific applications. Therefore, any prospective customers should satisfy themselves that the product is suitable for the environment in which it will be installed. Accordingly, Contar cannot take responsibility for the selection of a product unsuitable for the application. The information detailed in this communication is liable to change without prior notification. All resin floors are hand applied resulting in a surface texture that can vary.