

CONTOUR TRIONIC RADIATOR OUTPUT TABLE

Model: DeepClean Style: Flat Top - Floor Standing Features: Anti-ligature Grille



Rad Length (mm)	Casing Length (mm)	Rad Height (mm)	Type 11				Type 12			Type 22			
			400	500	600	750	500	600	750	400	500	600	750
			Casing Height (mm)	650	750	850	1000	750	850	1000	650	750	850
400	600	Art. Code	DSF116506-AL	DSF117506-AL	DSF118506-AL	DSF111006-AL	DSF127506-AL	DSF128506-AL	DSF121006-AL		DSF227506-AL	DSF228506-AL	DSF221006-AL
		Watts T50	223	269	314	379	340	394	472		461	533	636
500	700	Art. Code	DSF116507-AL	DSF117507-AL	DSF118507-AL	DSF111007-AL	DSF127507-AL	DSF128507-AL	DSF121007-AL		DSF227507-AL	DSF228507-AL	DSF221007-AL
		Watts T50	279	336	392	474	426	492	590		577	666	795
600	800	Art. Code	DSF116508-AL	DSF117508-AL	DSF118508-AL	DSF111008-AL	DSF127508-AL	DSF128508-AL	DSF121008-AL	DSF226508-AL	DSF227508-AL	DSF228508-AL	DSF221008-AL
		Watts T50	334	403	470	569	510	590	708	579	692	800	954
700	900	Art. Code	DSF116509-AL	DSF117509-AL	DSF118509-AL	DSF111009-AL	DSF127509-AL	DSF128509-AL	DSF121009-AL	DSF226509-AL	DSF227509-AL	DSF228509-AL	DSF228509-AL
		Watts T50	390	470	548	664	595	688	826	676	807	933	1,113
800	1000	Art. Code	DSF116510-AL	DSF117510-AL	DSF118510-AL	DSF111010-AL	DSF127510-AL	DSF128510-AL	DSF121010-AL	DSF226510-AL	DSF227510-AL	DSF228510-AL	DSF221010-AL
		Watts T50	446	538	626	758	680	786	944	773	922	1,066	1,272
900	1100	Art. Code	DSF116511-AL	DSF117511-AL	DSF118511-AL	DSF111011-AL	DSF127511-AL	DSF128511-AL	DSF121011-AL	DSF226511-AL	DSF227511-AL	DSF228511-AL	DSF221011-AL
		Watts T50	502	605	705	854	766	885	1,062	869	1,038	1,200	1,430
1000	1200	Art. Code	DSF116512-AL	DSF117512-AL	DSF118512-AL	DSF111012-AL	DSF127512-AL	DSF128512-AL	DSF121012-AL	DSF226512-AL	DSF227512-AL	DSF228512-AL	DSF221012-AL
		Watts T50	558	672	783	948	850	983	1,180	966	1,153	1,333	1,590
1100	1300	Art. Code	DSF116513-AL	DSF117513-AL	DSF118513-AL	DSF111013-AL	DSF127513-AL	DSF128513-AL	DSF121013-AL	DSF226513-AL	DSF227513-AL	DSF228513-AL	DSF221013-AL
		Watts T50	614	739	862	1,043	935	1,082	1,298	1,062	1,268	1,466	1,749
1200	1400	Art. Code	DSF116514-AL	DSF117514-AL	DSF118514-AL	DSF111014-AL	DSF127514-AL	DSF128514-AL	DSF121014-AL	DSF226514-AL	DSF227514-AL	DSF228514-AL	DSF221014-AL
		Watts T50	669	806	940	1,138	1,021	1,180	1,416	1,159	1,383	1,599	1,908
1400	1600	Art. Code	DSF116516-AL	DSF117516-AL	DSF118516-AL	DSF111016-AL	DSF127516-AL	DSF128516-AL	DSF121016-AL	DSF226516-AL	DSF227516-AL	DSF228516-AL	
		Watts T50	781	941	1,097	1,327	1,190	1,377	1,652	1,352	1,614	1,866	
1600	1800	Art. Code	DSF116518-AL	DSF117518-AL	DSF118518-AL		DSF127518-AL	DSF128518-AL		DSF226518-AL	DSF227518-AL	DSF228518-AL	
		Watts T50	892	1,075	1,254		1,361	1,574		1,545	1,845	2,133	
1800	2000	Art. Code	DSF116520-AL	DSF117520-AL	DSF118520-AL		DSF127520-AL	DSF128520-AL		DSF226520-AL	DSF227520-AL	DSF228520-AL	
		Watts T50	1,004	1,210	1,410		1,531	1,770		1,738	2,075	2,399	

Heat Outputs to BS EN 442 Certification.

Outputs based on a mean radiator water temperature of 70°C and a room temperature of 20°C - DELTA T 50°C

To Achieve Delta T60 increase T50 figures by 20.5%

Convert BTU to Watts x 0.293 : Convert Watts to BTU divide by 0.293

Casing Depths

Type 11	155mm
Type 12	165mm
Type 22	195mm

