

# MySmartBox specifications

<b>MODEL</b>	MySmartBox by Decayeux - Smart electronic parcel boxes unit
<b>CONTROL UNIT</b>	<ul style="list-style-type: none"> <li>• Courier identification</li> <li>• Recipient selection</li> <li>• Locker size selection</li> <li>• SMS notification or push notification</li> </ul>
<b>FINISH</b>	20 powder coated standard RAL colours. 2 different colours maximum by MySmartBox unit Optional : Custom printing on the boxes doors
<b>PARCEL BOXES UNIT</b>	<p>Unit made to requirements from 6 different locker sizes (S, M, L, XL, XL-h, XXL) Doors and body made of electro-galvanised steel Body thickness : 0.6mm (internal) or 2mm (external) Doors thickness : 1.2mm (internal) or 2mm (external)</p> <p><b>Freestanding or Wall-mounted installation</b> Aluminium structure with adjustable stabilisers 4 castor wheels (optional) External casing Mounting brackets</p> <p><b>Recessed installation</b> Aluminium structure Frame for recessed application.</p>
<b>LOCK(S)</b>	Lock(s) with electrical rotary latch R4-EM (Southco) Opening by automatic ejection
<b>SCREEN</b>	4,3" (10,9cm) Backlit capacitive touchscreen with 3mm protection glass Resolution 480x272 Luminosity : 300cd/m2. Idle time sleep mode
<b>INTEGRATED READER</b>	Omnidirectional barcode reader Fob reader or Keypad
<b>POWER SUPPLY</b>	Primary : 120-240V Ac - 60W • Secondary: 12V Dc
<b>COMMUNICATION GSM</b>	Tri-band GSM - Class 4 - 2W • SIM card provided • Integrated Antenna
<b>CORE SYSTEM</b>	32-bit processor • 2Gb micro SD card • USB interface • 1 to 6 boxes as default • Extension cards for 14 additional boxes available • CE , CEM & RoHS compliance
<b>SOFTWARE</b>	Remote residents and users management • Log book
<b>OPTIONAL</b>	Backup battery • SMS subscription • Aluminium surround • Castor wheels • Mailboxes



**DECAYEUX**  
SINCE 1872