

## Eco Weave 3920 (Broadloom)

Data Sheet: DOC 3920v1 01.11.2015

### NBS SPECIFICATION

#### M50 Rubber/Plastic/Cork/Lino/Carpet Tiling/Sheeting 170 Carpeting

|              |   |
|--------------|---|
| Manufacturer | danfloor Uk Limited, 106 Longmead Road, Emerald Park, Emersons Green, Bristol, BS16 7FG<br>Tel: 0333 014 3132, Fax: 0333 014 3134<br>Website: www.danfloor.co.uk, Email: sales@danfloor.co.uk |
| Reference    | Eco Weave 3920  |
| Backing      | Latex KT Bac / Textile TD Bac   |

### DETAILED SPECIFICATION

|                        |   |
|------------------------|---|
| Manufacturer           | danfloor Uk Limited, 106 Longmead Road, Emerald Park, Emersons Green, Bristol, BS16 7FG<br>Tel: 0333 014 3132, Fax: 0333 014 3134<br>Website: www.danfloor.co.uk, Email: sales@danfloor.co.uk |
| Reference              | Eco Weave 3920  |
| Backing                | Latex KT Bac / Textile TD Bac   |
| Construction           | Flat Woven  |
| Surface Yarn           | 100% Polyamide Nylon Solution Dyed ECONYL   |
| Pile Weight            | 560 g/m <sup>2</sup>  |
| Total Product Weight   | 2500 g/m <sup>2</sup> (KT Bac), 1800 g/m <sup>2</sup> (TD Bac)  |
| Dimensions             | 4.00 Mts wide   |
| Pile Height            | 2.00mm  |
| Total Carpet Thickness | 4.00mm (KT Bac), 3.00mm (TD Bac)  |
| Colours                | Available in 12 colours   |
| Classification         | BSEN 1307 Wear classification: 33 – Commercial  |
| Warranties             | 10 year wear warranty, 10 year anti-static warranty<br>Full warranty details available on request   |

### INSTALLATION INSTRUCTION

Recommended adhesive. F.Ball & Co. 01538 361633. Product - Permanent Bond F3, F40 or S910. Seaming F30.

All carpets should be laid in accordance with BS5325:2001 Installation of textile floorcovering.