

Evolution Forest 3666 1 (Textile Impervious Bac)

Data Sheet: DOC36661v1 28.09.2017

NBS SPECIFICATION

M50 Rubber/Plastic/Cork/Lino/Carpet Tiling/Sheeting 170 Carpeting

Manufacturer	danfloor Uk Limited, 106 Longmead Road, Emerald Park, Emersons Green, Bristol, BS16 7FG Tel: 0333 014 3132, Fax: 0333 014 3134 Website: www.danfloor.co.uk, Email: sales@danfloor.co.uk
Reference	Evolution Forest 3666 1
Backing	Textile Impervious Bac

DETAILED SPECIFICATION

Manufacturer	danfloor Uk Limited, 106 Longmead Road, Emerald Park, Emersons Green, Bristol, BS16 7FG Tel: 0333 014 3132, Fax: 0333 014 3134 Website: www.danfloor.co.uk, Email: sales@danfloor.co.uk
Reference	Evolution Forest 3666 1
Backing	Textile Impervious Bac
Construction	1/8" Gauge Tufted "Colorpoint LCL"
Surface Yarn	100% ECONYL® Regenerated Nylon 6 yarn
Pile Weight	1250 Grams/m ²
Total Product Weight	3250 Grams/m ²
Dimensions	4.00 Mts Wide
Pattern Repeat	200cm width, 100cm length
Pile Height	5.00mm
Total Carpet Thickness	7.50mm
Colours	Available in 9 colours
Classification	EN 1307 Wear classification: 33 – Commercial
Warranties	10 year wear warranty, 10 year anti-static warranty Full warranty details available on request
Breeam Certification	Awaiting Classification - Expected Autumn 2018

INSTALLATION INSTRUCTION

Recommended adhesive. F.Ball & Co. 01538 361633. Product - Permanent Bond F3, F40 or Release F2, F3, F40.

All carpets should be laid in accordance with BS5325:2001 Installation of textile floorcovering.