

product ref: 231B1-WM



Precision-engineered from aluminium and glass, with optically-bonded touchscreen and high-res graphics, Delmatic's 5" Touchpanel delivers the ultimate in touchscreen looks and experience.

Vibrant graphics provide powerful control of lighting and lighting scenes as well as other integrated services including window blinds and temperature set-point. Context-sensitive graphical screens provide intuitive operation and a wide choice of software configurable functions.

The TFT touchpanel provides high-resolution 800 x 480 graphics which are fully configurable with custom images, backgrounds and logos. Users can flip instantly between functions, effortlessly controlling lighting, blinds, shades, HVAC functions and other optional integrated services.

The 5" Touchpanel adopts the DALI protocol and up to sixteen Touchpanels can connect along a single DALI pair to a dedicated DALI controller.

### dimensions and mounting

134 mm (w) x 102 mm (h) x 13 mm (d) + 2 mm float.  
Mounts onto a standard single-gang switch backbox.

### power and data connections

Derives power from a 3.3V DC input (from PSU supplied).  
Communicates along a two-core DALI buswire.

### communications and data sharing

DALI lighting and scene commands are routed via the DALI network to the relevant luminaires. Window blind and HVAC commands are routed via the DALI controller and shared with the BMS via the router BACnet gateway.

### sample touchpanel graphics

