



Delta Membrane Systems Ltd

n5Plus



Delta® MS-Drain

By Delta Membrane Systems Ltd

Detailed description

High density polyethylene protection layer for basement waterproofing. The dimpled profile is covered with a geotextile, which provides a drainage route for groundwater.

Product guidance - As Standard

Composition

Dimpled high-density polyethylene sheet with a fused-on hydrophilic polypropylene geotextile.

Roll size:

2 x 30 m.

Drainage:

- Dimple height (approximate): 4 mm.
- Air gap (approximate): 2.6 L/m².
- Characteristic opening size (EN ISO 13433): 0.6 mm.
- Drainage capacity (approximate): 1.0 L/s.m.

Compressive strength:

300 kN/m².

Service temperature:

-30 to +80°C.

Product specification

Manufacturer

- Name:	Delta Membrane Systems Ltd
- Web:	www.deltamembranes.com
- Email:	info@deltamembranes.com
- Tel:	+44 (0)1992 523523
- Fax:	+44 (0)1992 523250
- Address:	Delta House,Merlin Way,North Weald,Epping,Essex CM16 6HR

Product reference

Delta® MS-Drain

Accessories

[Adhesive pins] - For fixing laps.
[Edge profile] - Top edge protector.
[Plastic percussion plug] - For fixing sheets when nails cannot be used.
[Terraxx screw] - For fixing sheets to insulation boards.