



Delta Membrane Systems Ltd

n55Plus



## Delta®-MS500

By Delta Membrane Systems Ltd

### Detailed description

Delta®-MS500 is a high density polyethylene (HDPE) studded membrane for use on walls, floors, vaults and tunnels as a waterproof system. It can also be used externally for waterproof protection of sub-ground structures. It provides excellent chemical resistance, is completely rot proof and prevents root penetration.

#### Joint lap:

70 mm plain edge to overlap three studs is recommended; all laps sealed with joint sealant.

### Product guidance - As Standard

#### Thickness:

- Membrane: 0.6 mm.
- Stud height: 8 mm.

#### Joint sealant:

- Delta Tape: 28 mm wide x 2 mm thick black butyl rubber tape for sealing joints in membrane.
- Delta Rope: 10 mm diameter black butyl rubber beading for sealing the membrane around pipes and openings, joining floor and wall membranes, and to form a gasket between the plug and membrane.

### Product specification

#### Manufacturer

- Name:	Delta Membrane Systems Ltd
- Web:	www.deltamembranes.com
- Email:	info@deltamembranes.com
- Tel:	+44 (0)1992 523523
- Fax:	+44 (0)1992 523250
- Address:	Delta House,Merlin Way,North Weald,Epping,Essex CM16 6HR

Product reference	Delta®-MS500
Colour	Clear Contractor's choice
Joint sealant	Delta-Tape to flanged joints Delta-Rope to studded joints