



Delta Membrane Systems Ltd

n55Plus



Delta-Lath

By Delta Membrane Systems Ltd

Detailed description

A dimpled membrane with a mesh face, providing a key for plaster, render or dab fixed plasterboard, available in brown or clear.

Features:

- The dimples form an air gap which insulates and allows for ventilation and natural drying of the wall.
- The air gap can be vented externally with the use of air vents, or internally using Delta-PT profiles fixed to the top and bottom of the wall.

Fixing:

- Delta-Lath is fixed to the wall with Lath plugs and sealed with Delta sealant.
- Sheets must be fixed along all edges and generally at not more than 250 mm vertical and horizontal staggered centres using Delta-PT Fixing Plugs and Delta Sealant or grommet. Alternatively, use the Delta-Qwik-Seal Plug.
- When used externally, fixing centres must be closed up to 150 mm.

Product guidance - As Standard

Compressive strength:

70 kN/m².

Weight:

530 g/m².

Stud height:

8 mm.

Roll width:

1500 mm.

Product specification

Manufacturer

- Name: Delta Membrane Systems Ltd
- Web: www.deltamembranes.com
- Email: info@deltamembranes.com
- Tel: +44 (0)1992 523523
- Fax: +44 (0)1992 523250
- Address: Delta House,Merlin Way,North Weald,Epping,Essex CM16 6HR

Product reference Delta-Lath

Colour Brown
Clear

Accessories [Delta-PT Fixing Plugs]
[Delta-PT Lath Plugs with grommet]
[Delta-Qwik-Seal Plug]
[Delta-PT Profiles]
[Delta Sealant]
[Flexidri Plus plugs]
[Flexidri plugs]