

April 2016



L20 SAMPLE SPECIFICATION NONE FIRE RATED DOORSET

Components

INTERNAL NONE FIRE RATED TIMBER DOORSETS:

Product Data Sheet reference: PDS1 Series 1

Manufacturer: Noberne Doors Ltd, Lupton Street, Hunslet, Leeds LS10 2QP

telephone: 0113 277 8577, email: sales@nobernedoors.co.uk

Door leaf:

Core: Solid 450kg/m³ flax core 63x36mm softwood perimeter frame

Door Thickness: 44mm thick

Facing: (MDF/veneer/laminate)

Lipping: (Visible/Concealed) 10mm hardwood lipping to all edges

Glazing details: None fire rated doors to be factory glazed with (6.4mm clear laminated safety glass) and (pinned/socket and screw) bolection beads.

Finish as delivered: Factory finished (one coat primer to two faces/two coats factory lacquer to two faces)

Frame:

Wood species: (Unsorted European Redwood/Hardwood)

Class (to BS EN 942): J40 and J50

Finish as delivered: (Primed for site painting/Sealer coat for site finish)

Preservative treatment: N/A

Moisture content on delivery: 9 to 13%

Architrave:

Wood Species: (MDF/Hardwood)

Class (to BS EN 942): J40 and J50

Preservative treatment: N/A

Moisture content on delivery: 9 to 13%

Ironmongery:

Door hung in frame on Noberne BZP lift off hinges 3 per door leaf

Perimeter seals:

N/A

Other requirements:

Fixing: In strict accordance with manufacturers instructions and BS8214 2008

Note: All doors to be labeled with manufacturers metal foil labels

Please amend (items) as required. We would be happy to review or discuss your specification requirements. Telephone 0113 2778577 or Email sales@nobernedoors.co.uk