

Door & side panel construction	GRP compression moulded skins. Choice of external colour, white internal. LVL engineered timber core with cross-grain construction.
Locking mechanism	A choice of Yale and GU Ferco multipoint locks. Stainless steel austenitic face plate. Inward opening doors tested to BS6375 & PAS024. Fully adjustable keepsets, integral latch snib.
PVC outerframe	A Door-Stop composite door outerframe specifically designed to work with 44mm door leafs Energy efficient recycled reinforcement.
Top box construction	One piece door frame with dedicated composite door transom bar.
Door slab edging	2mm PVC white edging with ash grain effect embossing all around. Trimmed and radiused edges to match door leaf. CNC routed to match radius of lock faceplate and hinges
Glazing cassette	Colour matched reglazable cassette
Hardware colour	Fully suited in gold, chrome, black, white, graphite or contemporary stainless.
Handle type	Lever/Lever colour suited to hardware selection
Hinge type	Adjustable in 2 dimensions or fixed butt.
Weather performance	BS6375 on inward opening doors BSI Kitemark if flag hinges upgrade is chosen
Security rating	PAS024 on inward opening doors BSI kitemark if flag hinges upgrade is chosen Q-Mark accreditation
Number of keys	3 or 5 (specific to lock)
Glass	24mm double glazed toughened sealed units. 24mm Low E sealed units used in top boxes and fully glazed panels
Standard cylinder	Conforms to PAS024:2016. Anti-bump Complies to Secured by Design Tested to BS EN 1303:2005 Available in nickel and brass
Tolerances	The manufacturing tolerances for composite doors and/or Side panels are compliant with the British Standard requirements of +/- 3mm.

OPTIONS

Hardware / Furniture	A choice of Stainless Steel or Fab & Fix fully suited hardware and furniture
Letterplate construction	All metal faceplates and surrounds, suited to match other furniture
Low threshold	Low PVC threshold, colour matched to the outerframe Low Aluminium part 'M' compliant with thermal break and available in white, brown and caramel
Extension profile	Available colour matched in measurements of 15mm, 25mm and 50mm
Fixed hinges	Fixed position butt hinges available.
Lever pad handle	Lever/pad and lever split spindle options available, suited to match other furniture