



# Safety Data Sheet

Dow Chemical Company Ltd

**Product Name:** FLOORMATE(TM) 700-A Extruded Polystyrene Foam

**Revision Date:** 2008/11/20

**Print Date:** 26 Nov 2012

Dow Chemical Company Ltd encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. Identification of the substance/preparation and of the company/undertaking

### Product Name

FLOORMATE™ 700-A Extruded Polystyrene Foam

### Use of the substance/preparation

Thermal insulation.

### COMPANY IDENTIFICATION

Dow Chemical Company Ltd  
Diamond House, Lotus Park  
Kingsbury Crescent  
TW18 3AG Staines, Middlesex  
United Kingdom

Customer Information Number: 0203 139 4000

[SDSQuestion@dow.com](mailto:SDSQuestion@dow.com)

For questions about this SDS, contact: [SDSQuestion@dow.com](mailto:SDSQuestion@dow.com)

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 0031 115 694 982

**Local Emergency Contact:** 00 31 115 69 4982

## 2. Hazards Identification

This product is not classified as dangerous according to EC criteria.

## 3. Composition/information on ingredients

Component	Amount	Classification:	CAS #	EC #
1,2,5,6,9,10-Hexabromocyclododecane (HBCD)	> 0.1 %	N: R50, R53	3194-55-6	221-695-9

See Section 16 for full text of R-phrases.

Extruded polystyrene foam containing a halogenated flame retardant system.

®(TM)\*Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

## 4. First-aid measures

**Eye Contact:** If irritation occurs, Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Skin Contact:** Wash skin with plenty of water.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Ingestion:** No emergency medical treatment necessary.

**Notes to Physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire Fighting Measures

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

**Unusual Fire and Explosion Hazards:** Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product contains a flame retardant to inhibit accidental ignition from small fire sources. This plastic foam product is combustible and should be protected from flames and other high heat sources. For more information, contact Dow. Dense smoke is produced when product burns.

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or flaming conditions, carbon monoxide, carbon dioxide and carbon are generated. Combustion products may include and are not limited to: Hydrogen bromide. Based on combustion toxicity testing, the effects of combustion from this foam are not more acutely toxic than the effects of combustion from common building materials such as wood.

## 6. Accidental Release Measures

**Steps to be Taken if Material is Released or Spilled:** Recover spilled material if possible. See Section 13, Disposal Considerations, for additional information.

**Personal Precautions:** There are no special required instructions.

**Environmental Precautions:** There are no special required instructions.

## 7. Handling and Storage

### Handling

**General Handling:** Fabrication methods which involve cutting into this product may release the blowing agent(s) remaining in the cells. Provide adequate ventilation to assure localized concentrations in release areas are maintained below the lower flammable limit. Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product is combustible and may constitute a fire hazard if improperly used or installed. When installed, this product should be adequately protected as directed by national building regulations or instructions in the specific application brochure.

### Storage

During shipment, storage, installation and use, this material should not be exposed to flame or other ignition sources. This material contains a halogenated flame retardant additive system to inhibit accidental ignition from small fire sources.

## 8. Exposure Controls / Personal Protection

### Exposure Limits

None established

Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

### Personal Protection

**Eye/Face Protection:** Eye protection should not be necessary. For fabrication operations safety glasses are recommended. Safety glasses should be consistent with EN 166 or equivalent. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

**Skin Protection:** No precautions other than clean body-covering clothing should be needed.

**Hand protection:** Use gloves to protect from mechanical injury. Selection of gloves will depend on the task.

**Respiratory Protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. When respiratory protection is required for certain operations, including but not limited to saw, router or hot-wire cutting, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

**Ingestion:** No precautions necessary due to the physical properties of the material.

### Engineering Controls

**Ventilation:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

## 9. Physical and Chemical Properties

<b>Physical State</b>	Board
<b>Color</b>	Blue
<b>Odor</b>	Odorless
<b>Flash Point - Closed Cup</b>	346 °C <i>Literature</i>
<b>Flammable Limits In Air</b>	<b>Lower:</b> Not applicable <b>Upper:</b> Not applicable
<b>Autoignition Temperature</b>	491 °C <i>Literature</i>
<b>Vapor Pressure</b>	Not applicable
<b>Boiling Point (760 mmHg)</b>	Not applicable.
<b>Vapor Density (air = 1)</b>	Not applicable
<b>Specific Gravity (H2O = 1)</b>	Not applicable
<b>Solid Density</b>	20 - 70 kg/m3 <i>Literature</i>
<b>Freezing Point</b>	Not applicable
<b>Melting Point</b>	> 75 °C <i>Literature</i>
<b>Solubility in Water (by weight)</b>	insoluble in water
<b>pH</b>	Not applicable
<b>Decomposition Temperature</b>	No test data available
<b>Kinematic Viscosity</b>	Not applicable

## 10. Stability and Reactivity

### Stability/Instability

Thermally stable at typical use temperatures.

**Conditions to Avoid:** Avoid temperatures above 300°C (572°F) Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

**Incompatible Materials:** Avoid contact with: Oxidizers. Aldehydes. Amines. Esters. Liquid fuels. Organic solvents.

### Hazardous Polymerization

Will not occur.

### Thermal Decomposition

Does not normally decompose. Evolution of small amounts of hydrogen halides occur when heated over 250°C (482°F). Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aromatic compounds. Aldehydes. Ethylbenzene. Hydrogen bromide. Polymer fragments. Under high heat, non-flaming conditions, small amounts of aromatic hydrocarbons such as styrene and ethylbenzene are generated.

## 11. Toxicological Information

### Acute Toxicity

#### Ingestion

Swallowing is unlikely because of the physical state. Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

#### Eye Contact

Solid or dust may cause irritation due to mechanical action. Fumes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation.

#### Skin Contact

Mechanical injury only. Essentially nonirritating to skin.

#### Skin Absorption

Skin absorption is unlikely due to physical properties.

#### Inhalation

Dust may cause irritation to upper respiratory tract (nose and throat). Fumes/vapors released during thermal operations such as hot wire cutting may cause respiratory irritation.

### Repeated Dose Toxicity

Additives are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

### Chronic Toxicity and Carcinogenicity

No relevant information found.

### Developmental Toxicity

No relevant information found.

### Reproductive Toxicity

No relevant information found.

### Genetic Toxicology

No relevant information found.

## 12. Ecological Information

### ENVIRONMENTAL FATE

#### Movement & Partitioning

No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000). In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material is expected to float.

### **Persistence and Degradability**

Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

### **ECOTOXICITY**

This product contains a substance which is classified as dangerous for the environment. However recent studies on aquatic organisms have shown that articles such as Extruded polystyrene (XPS) foams, while containing this substance, do not need to be classified for environmental danger.

## **13. Disposal Considerations**

All efforts to recycle material should be made. However, this material contains a halogenated flame retardant and should not be recycled with other non-flame retarded plastics. This material may be disposed of preferably by incineration under approved conditions or, in some countries, in approved landfills. Customers are advised to check their local legislation governing the disposal of waste materials. If incinerated, it is recommended that the flue gases be treated by a scrubber before exhausting to the atmosphere.

## **14. Transport Information**

### **ROAD & RAIL**

NOT REGULATED

### **OCEAN**

NOT REGULATED

### **AIR**

NOT REGULATED

### **INLAND WATERWAYS**

NOT REGULATED

## **15. Regulatory Information**

### **European Inventory of Existing Commercial Chemical Substances (EINECS)**

The components of this product are on the EINECS inventory or are exempt from inventory requirements.

### **EC Classification and User Label Information**

This product is not classified as dangerous according to EC criteria.

### **REACH Regulation (EC) No 1907/2006.**

This product is an article according to Article 3(3) which does not intentionally release substances and therefore does not require registration according to Article 7. This product contains a substance listed in the Candidate list for Authorization established in accordance with article 59(1): 1,2,5,6,9,10-Hexabromocyclododecane (HBCD).

## **16. Other Information**

### **Risk-phrases in the Composition section**

R50/53

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

### **Revision**

Identification Number: 62145 / 3005 / Issue Date 2008/11/20 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

*Dow Chemical Company Ltd urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.*