

# TECHNICAL DATA SHEET

|                          |  |
|--------------------------|--|
| <b>SYSTEM</b>            | <b>DUCOSLIDE triple telescopic manual</b>  |
| <b>DESCRIPTION</b>       | Permanent external solar shading consists of 3 telescopic moveable sliding panels.<br>Manually controlled  |
| <b>TRACK</b>             | High Quality maintenance free sliding track  |
| <b>PARTS</b>             | Top Track with two-wheeled trolley / top fixing plate and adjustable endstops<br>Toothed belt / Toothed belt lock / fixing plate<br>Bottom Track aluminium and synthetic conductor |
| <b>TOP TRACK</b>         | 30/47/3 (3x)   |
| <b>BOTTOM TRACK</b>      | 20/20/4 (3x)   |
| <b>MOTOR</b>             | None   |
| <b>MAX. WEIGHT</b>       | 60 kg( each panel)   |
| <b>MATERIAL</b>          | Aluminium : Al Mg Si 0,5   |
| <b>MAX. FRAME WIDTH</b>  | 1200mm   |
| <b>MIN. FRAME WIDTH</b>  | 550mm  |
| <b>SURFACE TREATMENT</b> | standard natural anodized (15- 20µm)<br>polyester powdercoated (60-80µm)   |
| <b>COLOURS</b>           | Bottom track All Ral colours or anodized finish / Top track anodized   |

