

Professional
Product Guide

Dulux
TRADE
Trade & Trusted

“...if you want to stand out, tell your customers you always use Dulux Trade products”

Trusted by Richard Hutton,
Professional Decorator



INCLUDES SELECTED
POLYCELL PRODUCTS

A BRAND FROM
AkzoNobel



Everything you need, at your fingertips

Inside this handy guide you'll find everything you need to know about every **Dulux Trade** product. With applications, benefits, technical details and useful tips for each product all in one convenient place, you're ready for any job.

For colour cards, detailed product guides and technical literature visit your local **Dulux Trade** stockist, visit www.duluxtrade.co.uk or call the Technical Advice Centre on **08444 817 818**.

**"From experience it's reliable...
you can guarantee
the covering"**

*Trusted by Nigel Cluskey,
Professional Decorator*



PRODUCT AREAS

Sustainability and Colour	4
Primers	10
Walls and Ceilings	20
Trim Products	28
Exteriors	36
Specialist Products	46
Pre-decorative	58
Woodcare	68

ADDITIONAL INFORMATION

Services	78
Quick Reference Guide	84

Symbols explained



Roller Conventional Spray Brush Tube Knife Airless Spray Cartridge Skimming Knife Aerosol



Recently updated product



Recently added to the Dulux Trade range



Available in Light & Space colours

PLEASE NOTE: All quoted touch dry times and recoat times are dependent upon temperature and humidity. Exterior masonry paint coverage figures are only an approximate guide due to the variation of different building surfaces and may be reduced.

Making a positive impact across the total value chain

We take a total value chain approach, working with customers, suppliers and leading thinkers.

We seek to make a positive impact wherever we can, to minimise any negative impacts and to encourage others to do the same.



“We have a critical role to play in reducing the environmental footprint associated with the use of our products and delivering innovations that allow our customers to work more sustainably”

Susan Kendall, UK & Ireland Sustainability Director,
ICI Paints AkzoNobel

Our ambitions

As a company we have set ourselves three challenging ambitions, covering the economic, environmental and social aspects of sustainability. By working with the people who use our products, our suppliers and leading thinkers, we aim to make a positive difference where it matters most.



WATER-BASED VS SOLVENT-BASED

The development of more water-based products is one of the most important steps towards reducing the environmental impact of paint. Water-based formulations are better for air quality, and have a lower carbon footprint due to the replacement of oil-based solvents with water.

These environmental benefits are achieved without compromising the quality of the finish. All water-based products in the **Dulux Trade** range deliver outstanding performance and durability. We continue to provide solvent-based formulations where necessary and all our products comply with the latest legislation on VOCs (volatile organic compounds).

From thousands of colours we hand pick the best for the job

Each of our colour cards features a range of shades expertly chosen for every type of real life project, enabling customers to choose colours with total confidence. You can pick them up from your **Dulux Trade** stockist; visit **www.duluxtrade.co.uk** or order by phone on **08444 817 818**.

Professional Colour Guide

Ranging from classic favourites to the latest contemporary trends, simply grouped in colour families for easy selection.



Heritage

A superb range of period colours that will complement any space. This elegant card is perfect for even the most discerning of customers.



Weathershield

A wide selection of colours for exterior masonry, wood and metal, specially selected for the outdoor environment and long lasting protection.



Commercial Colour Guide

Our colour experts designed this compact range specifically for the commercial property market. 72 hand picked colours that will work well in both large and small areas, with lots of neutrals and other easy to select colours.



The Colour Specifier

A wider selection of colours for large commercial projects, these colours are selected and grouped into two beautiful palettes. Each palette is cleverly organised on a grid, enabling simpler selection of coordinated colour schemes.



**“It speeds up
and simplifies
choosing the
right colour”**

*Trusted by Laurie Andrews,
Professional Decorator*





“It’s extra light from a can”

*Trusted by Ber Mundy,
Professional Decorator*

Light & Space from **Dulux Trade** has been specifically developed to utilise the natural light in a room in order to make a room feel lighter, brighter and more spacious. Its innovative formulation not only allows the use of up to 22%* less energy, but the unique light reflective colours mean rooms appear significantly brighter and more spacious.



Light & Space from **Dulux Trade** features ground-breaking **LumiTec** technology.

It uses highly reflective paint components that reflect substantially more light back into and around the room. In tests to compare light absorption values, walls decorated with **Light & Space** paint absorbed 8% of the visible light compared to conventional emulsion from the **Dulux Trade Colour Palette** which absorbed 16%.

Light absorption values

Dulux Trade Colour Palette v Light & Space colour of similar hue



Light absorption value = **16%**



Light absorption value = **8%**

*See back cover for full details

Light & Space Colour Range available
in five finishes:



- Everyday, standard product
- Great for low traffic areas that just need brightening up



- Sustainable alternative to Vinyl Matt[∅]
- 20% less embodied carbon[∅] with no compromise on performance



- Fashionable and stylish matt finish^{∅∅}
- Beautiful 'dead' flat finish
- Perfect for hiding surface imperfections in period properties



- Unrivalled durability in a matt or eggshell finish
- Perfect for high traffic areas such as hallways, corridors and stairwells
- Eggshell is great for areas of high condensation, bathrooms and kitchens

[∅]See back cover for full details

^{∅∅}Only available in Absolute White



Primers

Wood Products

	Place of application – Interior and Exterior Wood Surfaces		
	Hardwoods	Softwoods	Resinous Woods
Quick Drying Wood Primer Undercoat	✓	✓	
Wood Primer	✓	✓	
Aluminium Wood Primer			✓
Quick Drying MDF Primer Undercoat			
All Purpose Primer	✓	✓	

Metal Products

	Place of application – Interior and Exterior Metal Surfaces			
	Iron		Steel	
	Weathered but clean	New	Weathered but clean	New
Metalshield Quick Drying Metal Primer				
Metalshield Zinc Phosphate Primer	✓	✓	✓	✓
Metal Primer	✓	✓	✓	✓
Mordant Solution				
All Purpose Primer	✓	✓	✓	✓

Walls and Ceilings Products

	Place of application – Interior Wall and Ceiling Surfaces			
	Plaster			Limewash
	New & bare	Painted & cracked	Textured - aged & unpainted	
All Purpose Primer	✓			
Primer Sealer		✓	✓	✓
Stain Block Plus				✓
Alkali Resisting Primer	✓			
Ultra Grip Primer				
Super Grip Primer				

				Recoatable	Water/ Solvent-based
Creosote/Bitumen Coated Wood		MDF			
				2 hours	Water-based
				16-24 hours	Solvent-based
	✓			16-24/48 hours	Solvent-based
			✓	2 hours	Water-based
				6 hours	Solvent-based
				Recoatable	Water/ Solvent-based
Other Non-Ferrous Metals		Galvanised Steel			
Weathered but clean	New	Weathered	New		
✓	✓	✓	✓	4-6 hours	Water-based
		✓	✓	3 hours	Solvent-based
		✓	✓	6-10 hours	Solvent-based
			✓	Within 48 hours	Water-based
✓	✓	✓	✓	6 hours	Solvent-based
			Recoatable	Water/ Solvent-based	
Distemper	Masonry	Problem surfaces e.g. ceramic tiles			
	✓		6 hours	Solvent-based	
✓			16-24 hours	Solvent-based	
✓	✓		6-12 hours	Water-based	
	✓		16-24 hours	Solvent-based	
		✓	16 hours	Water-based	
		✓	4-6 hours	Water-based	

Primers

Dulux Trade Quick Drying Wood Primer Undercoat

A quick drying dual-purpose primer undercoat suitable for interior and exterior use

Water-Based

DATA SHEET 202



Key Benefits

For softwoods or hardwoods. Excellent adhesion and opacity.

Colour range	White
Pack sizes	1L, 2.5L, 5L
Touch dry	1 hour, dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 13m ² per litre on most surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Can be used with the **Dulux Trade** range of quick drying water-based finishes to offer a complete water-based system

Dulux Trade Wood Primer

A general purpose solvent-based primer for use on wood

Solvent-Based

DATA SHEET 201



Key Benefits

For interior and exterior use. Seals the surface to provide excellent adhesion.

Colour range	White
Pack sizes	1L, 2.5L, 5L
Touch dry	4-6 hours
Recoatable	After 16-24 hours
Coverage	Up to 15m ² per litre on most surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Can be used on either hardwoods or softwoods

Dulux Trade Aluminium Wood Primer

An aluminium pigmented primer for use on all types of wood and aged creosoted or bitumen coated surfaces

Solvent-Based

DATA SHEET 204



Key Benefits

Primes resinous wood.

Colour range	Silver
Pack sizes	1L, 2.5L, 5L
Touch dry	3-4 hours
Recoatable	After 16-24 hours. Allow 48 hours between coats for aged creosoted or bitumen coated surfaces
Coverage	Up to 17m ² per litre on most surfaces
Thinning	This product should not be thinned

- Can be used both inside and out on resinous timber or surfaces that are liable to bleed through a newly applied paint system, e.g. aged creosote or bitumen
- An ideal primer for use on fire damaged wood after thorough washing down

Dulux Trade Quick Drying MDF Primer Undercoat

Dual purpose primer and undercoat

Water-Based

DATA SHEET 205



Key Benefits

For MDF surfaces inside and outside.

Colour range	White
Pack sizes	2.5L
Touch dry	Dependent upon temperature and humidity
Recoatable	2 hours
Coverage	Up to 13m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- Quick drying
- Low odour
- Primes and undercoats in one

Primers

Metalshield Quick Drying Metal Primer

For use on new bright or weathered galvanised metal surfaces, both inside and out

Water-Based

DATA SHEET 510



Key Benefits

Seals and protects surface to provide excellent adhesion. Up to 8 years protection when used with **Metalshield** Gloss or Satin Finish.

Colour range	Grey
Pack sizes	1L, 5L
Touch dry	2-4 hours
Recoatable	4-6 hours
Coverage	Up to 18m ² per litre on most surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Also suitable for other non-ferrous metals
- No pre-treatment required for new surfaces
- Ensure all surfaces are sound, dry and free from grease, wax and oil
- Not recommended for use on heated surfaces, at temperatures below 10°C or in areas of high humidity or condensation

Metalshield Zinc Phosphate Primer

High performance, high build primer with excellent rust inhibiting performance, suitable for interior and exterior use

Solvent-Based

DATA SHEET 511



Key Benefits

Excellent adhesion. Up to 8 years protection when used with **Metalshield** Gloss or Satin Finish. Quick drying.

Colour range	Buff
Pack sizes	1L, 5L
Touch dry	2-3 hours
Recoatable	3 hours
Coverage	Up to 7m ² per litre on most surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- High build protection: 50-65 microns dry film thickness
- Can be used on heated surfaces up to 90°C
- For use with **Metalshield** Gloss or Satin Finish
- Suitable for use over hand cleaned iron and steel, blast clean surfaces, weathered or pre-treated galvanised steel

Dulux Trade Metal Primer

A general purpose primer for use on iron and steel

Solvent-Based

DATA SHEET 101



Key Benefits

Corrosion resistance. Seals and protects the surface.

Colour range	Grey
Pack sizes	1L, 2.5L, 5L
Touch dry	6-10 hours
Recoatable	6-10 hours
Coverage	Up to 10m ² per litre on most surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Based on non-toxic pigments
- For ferrous and suitably prepared non-ferrous metals
- Prevents rust attack

Dulux Trade Mordant Solution

Etches the surfaces of new, bright galvanised metal to provide adhesion for subsequent paint systems

Water-Based

DATA SHEET 509



Key Benefits

Etches galvanised metal.

Colour range	Blue/Green
Pack sizes	2.5L
Recoatable	Pre-treated surface should be overcoated within 48 hours

Primers

Dulux Trade All Purpose Primer

A general purpose primer for use on wood, metal and plaster both inside and outside

Solvent-Based

DATA SHEET 303



Key Benefits

Primes wood, metal and seals bare plaster. Provides good adhesion.

Colour range	Grey
Pack sizes	1L, 2.5L
Touch dry	6 hours
Recoatable	After 6 hours
Coverage	Wood: up to 8m ² per litre. Metal: up to 11m ² per litre. Plaster: up to 7m ² per litre
Thinning	Thinning not generally required

- Penetrates bare wood to protect and seal
- Contains a rust inhibitor to protect metal surfaces against corrosion

Dulux Trade Primer Sealer

Seals highly porous, dry friable interior surfaces

Solvent-Based

DATA SHEET 302



Key Benefits

Can be used as a sealer over soft distemper and limewash.

Colour range	Off White
Pack sizes	1L, 2.5L, 5L
Touch dry	8-12 hours
Recoatable	16-24 hours
Coverage	Up to 9m ² per litre on most surfaces
Thinning	Thinning not generally required

- For plaster surfaces
- Useful for bridging hairline cracks if a paint has mud cracked
- Aged, unpainted textured plaster surfaces such as ceilings should be treated with Primer Sealer prior to decorating

Dulux Trade Stain Block Plus

A 2-in-1 problem solving primer that seals and binds surfaces and blocks common stains

Water-Based

DATA SHEET 307



Key Benefits

Seals powdery, dry and friable surfaces, including limewash and distemper. Blocks stains caused by water, ink, smoke damage etc.

Colour range	White
Pack sizes	1L, 2.5L, 5L
Touch dry	Dependent on temperature and humidity
Recoatable	After 6-12 hours. Note – this product can usually be recoated within 6-8 hours – but on very porous surfaces a longer drying time may be required
Coverage	Up to 14m ² per litre. 2 coats may be required on severely stained surfaces
Thinning	This product should not be thinned

Dulux Trade Alkali Resisting Primer

For use on new, dry walls and ceilings that may contain alkalis

Solvent-Based

DATA SHEET 301



Key Benefits

Seals tobacco stains and smoke damage. Also for use as a primer for surfaces treated with fire retardant chemicals.

Colour range	Off White
Pack sizes	1L, 5L
Touch dry	8-12 hours
Recoatable	16-24 hours
Coverage	Up to 9m ² per litre on most surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Can be used as a primer on new, dry, interior plaster and masonry
- Holds back tobacco tar stains or smoke damage after thorough cleaning

Primers

Dulux Trade Ultra Grip Primer

A two-pack primer formulated to provide excellent adhesion to both interior and exterior surfaces

Water-Based

DATA SHEET 308



Key Benefits

Provides excellent adhesion when painting problem surfaces.

Colour range	White
Pack sizes	1L when mixed (0.8L Base 0.2L Activator)
Touch dry	4-6 hours at 20°C
Recoatable	Minimum 16 hours and maximum 7 days. Hard dry after 16 hours. Recoat within 7 days for optimum intercoat adhesion
Coverage	Up to 10m ² per litre
Thinning	Thinning not generally required. Please refer to data sheet for details

- For use on ceramic wall tiles, anodised aluminium, powder-coated metal etc.
- Suitable for interior and exterior use

Dulux Trade Super Grip Primer

An adhesion promoting primer for use both internally and externally

Water-Based

DATA SHEET 309



Key Benefits

Enables problem surfaces to be painted. Suitable for interior and exterior use.

Colour range	White
Pack sizes	1L, 2.5L, 5L
Touch dry	Dependent upon temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 18m ² per litre
Thinning	Thinning not generally required. Please refer to data sheet for details

- Provides good adhesion
- For use on ceramic tiles, melamine, glass, anodised aluminium etc.

Dulux
TRADE
Trade & Trusted

**“A particular
problem on a
job – there’ll
be a product
I can use”**

Trusted by Russ Pike,
Professional Decorator



A BRAND FROM
AkzoNobel

Walls and ceilings products

Dulux Trade decorative finishes offer the highest quality products delivering a variety of best in class properties, such as durability, coverage or spreading rate, to assist you in your internal decoration projects.

Walls and ceilings products

	Place of application – Interior Surfaces					
	General use	High traffic areas	Plaster Board		Plaster	
			Old	New	Dry	Not fully dry
Vinyl Matt	✓		✓	✓	✓	
Ecosure Matt	✓		✓	✓	✓	
Supermatt				✓		✓
Fast Matt			✓	✓	✓	
Vinyl Silk	✓		✓	✓	✓	
Vinyl Soft Sheen	✓		✓	✓	✓	
Diamond Matt	✓	✓	✓	✓	✓	
Durable Flat Matt		✓	✓	✓	✓	
Diamond High Performance		✓	✓	✓	✓	
Diamond Eggshell	✓	✓	✓	✓	✓	
Ecosure Quick Drying Eggshell	✓		✓	✓	✓	



						Recoatable	Water/ Solvent-based
Woodchip		Blown vinyl wall coverings		Masonry			
Old	New	Old	New	Old (Primed & Sealed)	New		
✓	✓	✓	✓	✓		2-4 hours	Water-based
✓	✓	✓	✓	✓		2-4 hours	Water-based
	✓		✓		✓	2-4 hours	Water-based
✓	✓	✓	✓	✓	✓	2-4 hours	Water-based
✓	✓	✓	✓	✓		2-4 hours	Water-based
✓	✓	✓	✓	✓		2-4 hours	Water-based
✓	✓			✓		4-6 hours	Water-based
✓	✓	✓	✓	✓		2-4 hours	Water-based
✓	✓	✓	✓	✓		4-6 hours	Water-based
✓	✓			✓		4-6 hours	Water-based
✓	✓	✓	✓	✓		4-6 hours	Water-based

Walls and Ceilings

Dulux Trade Vinyl Matt

A matt emulsion paint for use on interior walls and ceilings

Water-Based

DATA SHEET 411



LIGHT SPACE



Key Benefits

Excellent opacity and finish.

Colour range	PBW, White, Magnolia, Black, Gardenia and over 14,000 colours, including Colour Palette NCS2 and BS colours. Also available in the full Light & Space Colour range#
Pack sizes	1L*, 2.5L, 5L, 10L
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Ideal for use on woodchip, dry plaster and a range of building boards

#5L only. *Tinted bases only.

Dulux Trade Ecosure Matt

An environmentally focused^o matt finish for interior walls and ceilings

Water-Based

DATA SHEET 526



LIGHT SPACE



Key Benefits

Virtually zero VOCs and zero added solvents*. Low odour. Lower embodied carbon. High performance.

Colour range	PBW and over 14,000 colours, including Colour Palette , NCS2 and BS colours. Also available in Light & Space Absolute White**
Pack sizes	5L, 10L†
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Reduced VOC content
- 20% less embodied carbon^o

*PBW and some light colours only. Trace amounts of compounds may be found in components used in the paint such as colourants. **5L only. †PBW only. ^oCompared with **Dulux Trade Vinyl Matt 2011** formulation.

Dulux Trade Supermatt

A matt emulsion paint for use on interior walls and ceilings that are not fully dry

Water-Based

DATA SHEET 410



Key Benefits

Excellent opacity. Ideal for new plaster that is not fully dry.

Colour range	White, Magnolia and 150 tinted colours. Almond White and Gardenia are also available in ready mixed as 10L
Pack sizes	5L, 10L
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 18m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Ideal for use on new or skimmed interior plaster and interior masonry surfaces

Dulux Trade Fast Matt

A ready-for-use flat matt emulsion that is ideal for use on plasterboard

Water-Based

DATA SHEET 515



Key Benefits

Ideal for use in critical lighting conditions and for painting on plasterboard and dry lining.

Colour range	White, Magnolia and 150 tinted colours
Pack sizes	10L
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Easy application and less spatter
- Low sheen of product makes touch-in easy and gives an excellent finish

Walls and Ceilings

Dulux Trade Vinyl Silk

A silk emulsion paint for use on interior walls and ceilings

Water-Based

DATA SHEET 414



Key Benefits

Tough, wipeable finish. Good opacity and durability.

Colour range	PBW, White, Magnolia and over 14,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	2.5L, 5L, 10L
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Enhances low relief wall coverings and textured plaster
- Not suitable in areas subject to heavy condensation

Dulux Trade Vinyl Soft Sheen

A fashionable mid-sheen emulsion paint for use on interior walls and ceilings

Water-Based

DATA SHEET 413



Key Benefits

Wipeable. Tough, durable finish.

Colour range	PBW, Magnolia and over 14,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	1L*, 2.5L, 5L
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Ideal for use where a "Satin" finish is required

*Not all colours available in 1 litre.

Dulux Trade Diamond Matt

A tough, washable matt emulsion with superior durability

Water-Based

DATA SHEET 477



Improved Formula

LIGHT SPACE



Key Benefits

Now even more stain resistant formulation** and flatter finish

Colour range	PBW, Magnolia and over 12,000 colours*, including Colour Palette , NCS2 and BS colours. Also available in the full Light & Space Colour range*
Pack sizes	2.5L, 5L
Touch dry	Dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Improved formulation delivering even greater durability and stain resistance
- Even flatter matt finish, perfect for hiding surface imperfections
- Tough and wipeable

#5L only. *For availability in very deep colours, please contact the **Dulux Trade** Technical Advice Centre.

**The improved formulation only applies to PBW, Light Base, Magnolia and Medium Base.

Dulux Trade Durable Flat Matt

A fashionable flat matt finish for use on walls and ceilings

Water-Based

DATA SHEET 440



LIGHT SPACE



Key Benefits

A high quality, durable, completely flat finish with excellent opacity and coverage.

Colour range	White and over 14,000 colours, including Colour Palette , NCS2 and BS colours. Also available in Light & Space Absolute White**
Pack sizes	2.5L†, 5L
Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Ideal for period and contemporary properties
- Perfect at hiding imperfections

*5L only. †White only. #Only available in Flat Matt.

Walls and Ceilings

Diamond High Performance

For use on super high traffic areas including stairwells, corridors, waiting rooms, reception areas, retail interiors, gyms and changing rooms

Water-Based

DATA SHEET 545



New Product



Key Benefits

New extra tough Diamond High Performance is even more durable and 43% more scuff resistant than Standard Diamond Eggshell, so the beautiful eggshell finish will stand up to repeated cleaning and stay looking good for longer – even in super high traffic areas.

Colour range	PBW, Magnolia and over 3,000 colours, including Colour Palette, NCS2 and BS colours
Pack sizes	5L
Touch dry	Dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- A breakthrough in paint technology
- 5x tougher than standard Diamond Eggshell
- Tough and washable mid-sheen finish

Dulux Trade Diamond Eggshell

For use on interior walls, ceilings and woodwork

Water-Based

DATA SHEET 408



LIGHT SPACE



Key Benefits

Excellent adhesion, durability and stain resistance.

Colour range	PBW, Magnolia* and over 14,000 colours, including Colour Palette, NCS2 and BS colours. Also available in the full Light & Space Colour range*
Pack sizes	1L, 2.5L, 5L
Touch dry	Dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- 10x more stain resistant than standard water-based eggshells
- Tough, durable mid-sheen finish with superior stain resistance

*5L only.

Ecosure Quick Drying Eggshell

Environmentally focused durable mid-sheen finish
for walls, ceilings and woodwork

Water-Based

DATA SHEET 535



Key Benefits

Tough, durable finish. Ideal for kitchens and bathrooms. Lower VOC content and lower embodied carbon*.

Colour range	PBW and over 14,000 colours, including Colour Palette, NCS2 and BS colours
Pack sizes	5L
Touch dry	Dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- 10% less CO₂ emissions than Diamond Eggshell
- Minimum 20% VOC reduction vs. Diamond Eggshell
- 10x tougher than **Ecosure** Matt

*Compared with **Dulux Trade** Diamond Eggshell (2009 formulation).

Trim Products

Whether revitalising interior trim or painting from new, **Dulux Trade** offers the highest quality paints to assist you in achieving a beautiful lasting finish.

Trim Products

	Place of application				
	Interior Surfaces				
	Masonry	Wood		Metal	
General use		New	General use	New	
Ecosure Undercoat		✓	✓	✓	✓
Ecosure Gloss		✓	✓	✓	✓
Undercoat	✓	✓	✓	✓	✓
High Gloss	✓	✓	✓	✓	✓
New Work Undercoat			✓		✓
New Work Gloss			✓		✓
Satinwood		✓	✓	✓	✓
Diamond Satinwood		✓	✓	✓	✓
Eggshell		✓	✓	✓	✓



Heated Surfaces (e.g. radiators)	Exterior Surfaces			Recoatable	Water/ Solvent- based
	Masonry	Wood	Metal		
				6 hours	Water-based
				6 hours	Water-based
✓	✓	✓	✓	6-16 hours	Solvent-based
✓	✓	✓	✓	16-24 hours	Solvent-based
				6-16 hours	Solvent-based
				16-24 hours	Solvent-based
				16-24 hours	Solvent-based
				6 hours	Water-based
				16-24 hours	Solvent-based

Trim

Ecosure Undercoat

A professional quality, durable and quick drying undercoat with good opacity and adhesion properties

Water-Based

DATA SHEET 528



Key Benefits

Durable, quick drying with good opacity.

Colour range	PBW plus 18 tinted colours
Pack sizes	2.5L, 5L*
Touch dry	Dependent on temperature and humidity
Recoatable	6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Suitable for interior wood and metal
- 30% less embodied carbon when undercoat and gloss used as a system[^]
- Up to 72% less VOC content[^]

*PBW only. [^]Compared with **Dulux Trade** solvent-based variants as the market is over 82% solvent-based and 93% for gloss specifically.

Tip: To get the best from the **Ecosure** Gloss system, lightly dampen both a synthetic brush and the surface before application to increase the flow out.

Ecosure Gloss

A professional quality, quick drying and high sheen finish with good flow and application properties

Water-Based

DATA SHEET 527



Key Benefits

Non-yellowing, quick drying, durable high sheen finish.

Colour range	PBW and more than 5,000 colours, including Colour Palette and BS colours
Pack sizes	2.5L, 5L*
Touch dry	Dependent on temperature and humidity
Recoatable	6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Excellent flow and application
- Non-yellowing
- 30% less embodied carbon when **Ecosure** undercoat and gloss used as a system[^]
- Up to 72% less VOC content[^]

*PBW only. [^]Compared with **Dulux Trade** solvent-based variants as the market is over 82% solvent-based and 93% for gloss specifically.

Tip: To get the best from the **Ecosure** Gloss system, lightly dampen both a synthetic brush and the surface before application to increase the flow out.

Dulux Trade Undercoat

The ideal foundation for Dulux Trade High Gloss

Solvent-Based

DATA SHEET 404



Key Benefits

Low sheen level. Excellent flow out of brushmarks. Provides good build and obliteration.

Colour range	PBW, White, Dark Grey and 17 tinted colours
Pack sizes	1L, 2.5L, 5L
Touch dry	2-6 hours
Recoatable	After 6-16 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Retains good "cling" to sharp edges
- Can also be used with **Dulux Trade** Eggshell and Satinwood to provide surface obliteration over strong colours or poor surfaces

Dulux Trade High Gloss**

For general use on interior wood, metal and masonry surfaces

Solvent-Based

DATA SHEET 403



Key Benefits

Tough durable finish. Excellent flow out of brushmarks. Will withstand repeated washing.

Colour range	PBW, White and Black and more than 14,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	1L, 2.5L, 5L
Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 18m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Good opacity
- Resistant to mild chemical fume attack
- Can be used on heated surfaces, e.g. hot water pipes and radiators

see back page. For long-lasting whiteness, we recommend the use of a water-based formulation such as **Dulux Trade Ecosure Gloss.

Dulux Trade New Work Undercoat

Specifically formulated for the demanding requirements of new substrates

Solvent-Based

DATA SHEET 422



Key Benefits

Superb obliteration and edge coverage with excellent filling and levelling properties.

Colour range	White only
Pack sizes	5L
Touch dry	After 2-6 hours
Recoatable	6-16 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- The ideal partner for **Dulux Trade** New Work Gloss

Dulux Trade New Work Gloss**

Specifically formulated for the demanding requirements of new substrates

Solvent-Based

DATA SHEET 424



Key Benefits

Excellent coverage and opacity, with good flow out of brush marks.

Colour range	White only
Pack sizes	5L
Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 18m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please see data sheet for details

- Excellent intercoat adhesion to **Dulux Trade** New Work Undercoat

see back page. For long-lasting whiteness, we recommend the use of a water-based formulation such as **Dulux Trade Ecosure Gloss.

Dulux Trade Satinwood**

For use on interior wood and metal

Solvent-Based

DATA SHEET 406



Key Benefits

Fashionable satin finish. Does not normally require undercoat. Tough, durable finish.

Colour range	PBW and more than 14,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	1L, 2.5L, 5L
Touch dry	After 4-6 hours
Recoatable	After 16-24 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Will withstand repeated washing

see back page. For long-lasting whiteness, we recommend the use of a water-based formulation such as **Dulux Trade Diamond Satinwood.

Diamond Satinwood

For use on interior wood and metal

Water-Based

DATA SHEET 521



Key Benefits

Tough, durable satin finish. Ultimate durability.

Colour range	PBW and more than 10,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	1L, 2.5L, 5L*
Touch dry	Dependent on temperature and humidity
Recoatable	6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- The ideal partner for **Dulux Trade** Diamond Matt emulsion paint
- Non-yellowing

*Bases are only available in 2.5L

Dulux Trade Eggshell**

A tough, durable, mid-sheen finish for interior wood and metal

Solvent-Based

DATA SHEET 405



Key Benefits

Tough, durable finish that does not normally require undercoat.

Colour range	PBW, White and more than 14,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	1L*, 2.5L, 5L
Touch dry	4-6 hours
Recoatable	After 16-24 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please see data sheet for details

- Will withstand repeated washing
- Mild chemical resistance
- Low odour

*Only available in bases.

see back page. For long-lasting whiteness, we recommend the use of a water-based formulation such as **Dulux Trade Diamond Eggshell.

**“Good finished
quality and
easier to
work with”**

*Trusted by Craig Smith,
Professional Decorator*



Exterior Products

By using the **Weathershield** range, you can be confident that you have the ultimate exterior protection, with durability that lasts up to 15 years for exterior masonry paints and up to 8 years on exterior woodwork.

Exterior Products

	Place of application		
	Masonry		Render
	Sound & Dry	Dry & Friable	Sound & Dry
Smooth Masonry Paint	✓		✓
Textured Masonry Paint	✓		✓
Maximum Exposure	✓		✓
All Seasons Masonry Paint	✓		✓
All Seasons Masonry Gloss	✓		✓
Quick Drying Exterior Undercoat			
Quick Drying Exterior Gloss			
Quick Drying Satin			
Preservative Primer + ^{FP1}			
Exterior Flexible Undercoat			
Exterior High Gloss			
Stabilising Primer		✓	
Exterior Flexible Filler	✓		
Multi-Surface Fungicidal Wash	✓		



Joinery		Smooth Planed Wood		Touch Dry	Water/ Solvent- based
General Use	New or Bare	General Use	New or Bare		
				30 mins	Water-based
				1-2 hours	Water-based
				30 mins	Water-based
				30 mins	Solvent-based
				4 hours	Solvent-based
✓		✓		1-2 hours	Water-based
✓		✓		2 hours	Water-based
✓		✓		1-2 hours	Water-based
	✓		✓	24 hours	Water-based
✓		✓		2-6 hours	Solvent-based
✓		✓		4-6 hours	Solvent-based
				8-12 hours	Solvent-based
✓		✓		2 hours	Water-based
✓		✓		n/a	Water-based

Exteriors

Weathershield Smooth Masonry Paint

A quick drying water-based exterior masonry paint providing a smooth finish

Water-Based

DATA SHEET 418



Key Benefits

Excellent opacity and application with up to 15 years weather protection. Shower resistant in 30 minutes. Stays cleaner for longer.

Colour range	PBW, Magnolia, 5 ready mixed colours and 420 lightfast optimised tinted colours from the Weathershield fandeck as well as a range of NCS2, RAL and BS colours
Pack sizes	2.5L, 5L, 10L
Touch dry	30 minutes
Recoatable	After 2-4 hours dependent on temperature and humidity
Coverage	On smooth surfaces of low porosity e.g. rendering: 14-16m ² per litre On textured surfaces of low porosity e.g. pebbledash: 4-6m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- For smooth exterior walls, including: blockwork, concrete, stonework, cement, rendering, roughcast, pebbledash and also brickwork (not common or fletton)
- Contains a fungicide and algicide to help protect against the disfiguring effect of surface growth

Weathershield Textured Masonry Paint

A quick drying water-based exterior masonry paint providing a textured finish

Water-Based

DATA SHEET 419



Key Benefits

Up to 10 years weather protection. Helps bridge fine hairline cracks.

Colour range	PBW and 420 lightfast optimised tinted colours from the Weathershield fandeck as well as a range of NCS2, RAL and BS colours
Pack sizes	5L, 10L*
Touch dry	1-2 hours
Recoatable	After 2-4 hours
Coverage	On smooth surfaces of low porosity, e.g. rendering: 6-8m ² per litre. On textured surfaces of low porosity, e.g. pebbledash: 3-4m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- For a textured finish on exterior walls, including: blockwork, concrete, stonework, cement rendering, roughcast, pebbledash and also brickwork (not common or fletton)
- Contains a fungicide and algicide to help protect against the disfiguring effect of surface growth

*Ready mixed colours only.

Weathershield Maximum Exposure Smooth Masonry Paint

Smooth masonry paint offering excellent durability and protection even in harsh and demanding environments

Water-Based

DATA SHEET 522



Key Benefits

Ideal for harsh and demanding environments giving up to 15 years weather protection. Shower resistant in 15 minutes.

Colour range	PBW and 420 lightfast optimised tinted colours from the Weathershield fandeck as well as a range of NCS2, RAL and BS colours
Pack sizes	5L
Touch dry	30 minutes
Recoatable	2-4 hours dependent on temperature and humidity
Coverage	On smooth surfaces: 12-14m ² per litre. On textured surfaces: 4-6m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- Adhesion promoted. Salt/chemical spray resistant
- Contains fungicide to help protect against the disfiguring effect of mould growth on its film
- Application from 7°C
- Also 5x more flexible than standard **Dulux Trade** masonry paint

Tip: Before applying **Weathershield** Maximum Exposure, check the weather conditions and the temperature of the substrate to ensure that the product will cure thoroughly. Remember, it can only cure properly at temperatures above 7°C.

Weathershield All Seasons Masonry Paint

Quick drying smooth finish helping to extend the outdoor decorating season on exterior masonry

Solvent-Based

DATA SHEET 420



Key Benefits

Application during the winter months down to 5°C. Up to 15 years weather protection. Shower resistant in 15 minutes.

Colour range	PBW, Magnolia, Black and 225 lightfast optimised tinted colours from the Weathershield fandeck as well as a range of NCS2, RAL and BS colours
Pack sizes	4.5L, 5L*
Touch dry	30 minutes
Recoatable	After 1-2 hours
Coverage	On smooth surfaces of low porosity, e.g. rendering: 14-16m ² per litre. On textured surfaces of low porosity, e.g. pebbledash: 4-6m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- For use on exterior walls, including: blockwork, concrete, stonework, cement rendering, roughcast, pebbledash and also brickwork (not common or fletton)
- Contains a fungicide and algicide to help protect against the disfiguring effect of surface growths

*Ready mixed colours only.

Weathershield All Seasons Masonry Gloss

Quick drying, high-shine finish helps to extend the outdoor decorating season on exterior walls

Solvent-Based

DATA SHEET 429



Key Benefits

Application during the winter months down to 5°C. Up to 10 years weather protection. Excellent opacity.

Colour range	PBW, Magnolia, Gardenia and 225 lightfast optimised tinted colours from the Weathershield fandeck as well as a range of NCS2, RAL and BS colours
Pack sizes	4.5L, 5L*
Touch dry	4 hours
Recoatable	After 16 hours
Coverage	On smooth surfaces of low porosity, e.g. rendering: 14-16m ² per litre. On textured surfaces of low porosity, e.g. pebbledash: 4-6m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- For use on exterior walls, including: blockwork, concrete, stonework, cement, rendering, roughcast, pebbledash and also brickwork (not common or fletton)
- Contains a fungicide to help protect against the disfiguring effect of mould growths on its film

*Ready mixed colours only.

Weathershield Quick Drying Exterior Undercoat

Quick drying, water-based undercoat for exterior trim and woodwork

Water-Based

DATA SHEET 531



Key Benefits

Up to 6 years weather protection. Quick drying water-based formulation flexes with the wood to prevent cracking.

Colour range	PBW and 18 tinted colours
Pack sizes	1L, 2.5L, 5L*
Touch dry	1-2 hours dependent on temperature and humidity
Recoatable	2-4 hours dependent on temperature and humidity
Coverage	Up to 16m ² on most surfaces
Thinning	Thinning not generally required

- Provides excellent opacity
- Quick drying easy clean up

*PBW only.

Weathershield Quick Drying Exterior Gloss

A durable water-based quick drying exterior gloss, giving up to 6 years protection

Water-Based

DATA SHEET 534



Key Benefits

Up to 6 years weather protection. High gloss finish with excellent opacity. Flexes with wood to prevent cracking.

Colour range	PBW and over 620 tinted colours
Pack sizes	1L, 2.5L, 5L
Touch dry	2 hours
Recoatable	4 hours
Coverage	up to 16m ²
Thinning	This product should not be thinned

- Quick drying, easy clean up
- Excellent flowout of brush marks

Tip: When applying any water-based gloss or satin, always use a synthetic bristle brush and dampen the surface you are painting before applying the product.

Weathershield Quick Drying Satin

A trim product that has the flexibility and durability of the Weathershield system

Water-Based

DATA SHEET 428



Key Benefits

Up to 6 years weather protection. Quick drying and easy to apply.

Colour range	PBW and over 620 tinted colours
Pack sizes	1L*, 2.5L, 5L**
Touch dry	1-2 hours
Recoatable	After 2-4 hours
Coverage	Up to 20m ² per litre on most surfaces
Thinning	This product should not be thinned

- Contains a fungicide to help protect against the disfiguring effect of mould growth on its film

*Tinted colours only.

**PBW only.

Exteriors

Weathershield Preservative Primer+ (BP)[†]

A water based preservative basecoat for use with the Weathershield Exterior Gloss System

Water-Based

DATA SHEET 540



Key Benefits

Penetrates deep into the wood to seal and preserve against water damage, decay and blue stain fungi.

Colour range	Light green tint
Pack sizes	1L, 2.5L, 5L
Touch dry	Up to 24hrs
Recoatable	Allow the previous coat to soak in before applying the next
Coverage	4-5m ²
Thinning	This product should not be thinned

- This product is replacing the **Weathershield Aquatech** Preservative Basecoat+ as step 1 of the WEGS System
- Provides a sound basecoat for **Weathershield** Exterior Flexible Undercoat and High Gloss

Tip: This primer is water-based, protects from decay as well as blue stain and it is better for the environment. It also has green tint to help visualise treated areas.

*Our WEGS system is accredited by the British Board of Agrément. In normal conditions Dulux Trade Weathershield Exterior Gloss System will have good colour stability and perform satisfactorily for up to 8 years.
†see back page for details

Weathershield Exterior Flexible Undercoat

A flexible exterior undercoat for use with Weathershield Exterior High Gloss

Solvent-Based

DATA SHEET 402



Key Benefits

Up to 8 years weather protection. Flexes with the wood to prevent cracking.

Colour range	PBW, Dark Grey and 17 tinted colours
Pack sizes	1L, 2.5L, 5L
Touch dry	2-6 hours
Recoatable	Brilliant White and Dark Grey: 6-8 hours; all other colours: 16-24 hours
Coverage	Up to 16m ² per litre on most surfaces
Thinning	This product should not be thinned

- Provides good build and excellent opacity
- Can also be used on primed metal such as fences, pipes and garage doors
- For the best results, you should always use the correct system to ensure maximum durability

*Our WEGS system is accredited by the British Board of Agrément. In normal conditions Dulux Trade Weathershield Exterior Gloss System will have good colour stability and perform satisfactorily for up to 8 years.

Weathershield Exterior High Gloss

For general use on exterior joinery and smooth planed wood

Solvent-Based

DATA SHEET 401



Key Benefits

Up to 8 years weather protection. Easy to apply.

Colour range PBW, Black and more than 4000 tinted colours

Pack sizes 1L, 2.5L, 5L

Touch dry 4-6 hours

Recoatable 16-24 hours

Coverage Up to 18m² per litre on most surfaces

Thinning This product should not be thinned

- Provides an excellent high gloss finish
- Can also be used on plastic gutters, pipes and primed metal such as garage doors
- Contains a fungicide to help protect against the disfiguring effect of mould growths on its film

Tip: To get up to 8 years weather protection, you should always use the recommended system. For previously painted surfaces, apply one coat of undercoat and two coats of the gloss for a perfect gloss finish.

*Our WEGS system is accredited by the British Board of Agrément. In normal conditions Dulux Trade Weathershield Exterior Gloss System will have good colour stability and perform satisfactorily for up to 8 years.

Weathershield Stabilising Primer

A ready-to-use sealer for use with the Weathershield range of masonry paints

Solvent-Based

DATA SHEET 304



Key Benefits

Stabilises powdery masonry surfaces.

Colour range Clear

Pack sizes 2.5L, 5L

Touch dry 8-12 hours dependent on temperature and humidity

Recoatable 16-24 hours

Coverage Up to 12m² per litre on most surfaces

Thinning This product should not be thinned

- Use only on dry exterior masonry that remains powdery and friable after thorough preparation
- Do not seal sound, new or bare surfaces

Exteriors

Weathershield Exterior Flexible Filler

Exterior filler for filling in open joints, splits and minor cracks in wood and masonry surfaces

Water-Based

DATA SHEET 802



Key Benefits

Superior flexibility to resist shrinking and cracking. Easy to sand.

Colour range	Light Grey
Pack sizes	200g, 450g
Touch dry	2 hours depending on depth of the repair
Thinning	This product should not be thinned, but can be made easier to apply by adding a few drops of water

- Can be used with most **Dulux Trade** interior finishes
- Not suitable for use with varnish systems or woodstains
- Not to be used as a fine surface filler or for major repairs

Weathershield Multi-Surface Fungicidal Wash

A fungicidal wash for cleaning wood and masonry surfaces

Water-Based

DATA SHEET 803



Key Benefits

Kills algae and limits mould growth.

Colour range	Clear
Pack sizes	5L
Coverage	Up to 25m ² per litre
Thinning	This product should not be thinned

- Registered with the HSE*
- Can be used both inside and out with most **Dulux Trade** and **Weathershield** decorative paint systems, to give improved performance in areas subject to attack from surface growths

*Registered pesticide

**“It basically covers
whatever the surface
we are painting on
much better”**

Trusted by Jason Margetts,
Professional Decorator



Specialist Products

In demanding commercial environments, the innovative range of specialist products from **Dulux Trade** offers you high performing solutions to extend maintenance cycles.

Specialist Products

	Place of application		
	Interior Walls and Ceilings	Exterior Concrete Walls	
		Bare	Painted
Sterishield Diamond Matt	✓		
Sterishield Quick Drying Eggshell	✓		
Dry Fall Eggshell	✓		
Blockfiller Plus	✓	✓	
Cladshield			
Pyroshield Basecoat	✓		
Pyroshield Durable Matt	✓		
Pyroshield Durable Eggshell	✓		
Metalshield Gloss Finish			
Metalshield Satin Finish			
Floorshield			
High Performance Floor Paint			
Anti-Graffiti Sealer		✓	
Anti-Graffiti Primer	✓	✓	✓
Anti-Graffiti Finish	✓	✓	✓
Line Marking Paint			
Mouldshield Fungicidal Matt	✓		
Mouldshield Fungicidal Eggshell	✓		
Cellar Paint	✓		



Cladding	Metal	Floors e.g. Wood, Concrete, Steel etc.	Recoatable	Water/ Solvent- based
			2-4 hours	Water-based
			2-4 hours	Water-based
			2 hours	Water-based
			4 hours	Water-based
✓			4-6 hours	Water-based
			12 hours	Water-based
			2-4 hours	Water-based
			2-4 hours	Water-based
	✓		4-6 hours	Solvent-based
	✓		4-6 hours	Solvent-based
		✓	12-16 hours	Solvent-based
		✓	16-24 hours	Water-based
			16 hours	Water-based
			16 hours	Water-based
			16 hours	Water-based
		✓	1 hour	Solvent-based
			4-6 hours	Water-based
			4-6 hours	Water-based
			2-16 hours	Solvent-based

Specialist Products

Sterishield Diamond Matt[#]

A quick drying water-based matt emulsion, containing an in-film bactericide which inhibits bacteria. Suitable for all normal interior wall and ceiling surfaces

Water-Based

DATA SHEET 519



Key Benefits

Helps to promote a more hygienic environment. A washable, durable and stain resistant matt formulation.

Colour range	More than 10,000 colours, including Colour Palette , NCS2 and BS colours*
Pack sizes	5L
Touch dry	Dependent upon temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 16m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- When combined with appropriate cleaning practices, **Sterishield Diamond Matt** helps to promote a more hygienic environment
- Proven to reduce bacterial populations of MRSA, E-Coli, and Pseudomonas Aeruginosa over a 12-hour period
- Silver bactericide actively inhibits bacteria

Tip: **Sterishield** actually increases its activity against bacteria when washed and scrubbed.

*For availability in very deep colours please contact the **Dulux Trade** Technical Advice Centre.

[#]**Steishield** from **Dulux Trade** is not substitute for good hygiene practices.

Sterishield Quick Drying Eggshell[#]

A quick drying water-based mid-sheen emulsion, containing an in-film bactericide which inhibits bacteria. Suitable for all normal interior wall and ceiling surfaces

Water-Based

DATA SHEET 520



Key Benefits

Helps to promote a more hygienic environment. Tough, washable and durable mid-sheen formulation.

Colour range	More than 10,000 colours, including Colour Palette , NCS2 and BS colours
Pack sizes	5L
Touch dry	Dependent upon temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 17m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- Formulated to reduce bacterial populations of MRSA, E-Coli, and Pseudomonas Aeruginosa over a 12-hour period
- Silver bactericide actively inhibits bacteria
- Durable washable eggshell finish

Tip: **Sterishield** actually increases its activity against bacteria when washed and scrubbed.

[#]**Steishield** from **Dulux Trade** is not substitute for good hygiene practices.

Dulux Trade Dry Fall Eggshell

A mid-sheen emulsion paint for use on commercial ceilings and walls

Water-Based

DATA SHEET 444



Key Benefits

Overspray dries to a dust before reaching the floor.*

Colour range	White
Pack sizes	10L
Touch dry	30 minutes
Recoatable	2 hours
Coverage	Up to 9m ² per litre
Application	This product is formulated for airless spray only
Thinning	Thinning not generally required

- Excellent finish, high opacity
- Very good adhesion, quick drying

*On drop of 10 feet/3.3m at 25°C and 50% RH.

Dulux Trade Blockfiller Plus

Fills minor imperfections and upgrades the appearance of concrete and concrete blocks to achieve a smooth finish

Water-Based

DATA SHEET 448



Key Benefits

One-coat, high opacity formulation saves time and money.

Colour range	White
Pack sizes	10L
Touch dry	1 hour
Recoatable	4 hours
Coverage	5m ² per litre depending upon the porosity of the substrate
Application	Apply by airless spray then back roll to fill all voids and holes. May also be applied by brush or roller
Thinning	This product should not be thinned

- Can be top coated with a range of finishes
- Fast and effective spray and back rolling application

Specialist Products

Cladshield

A water-based formulation offering up to 8 years rust protection for cladding

Water-Based

DATA SHEET 532



Key Benefits

Single pack solution. Extends maintenance cycles on external steel cladding. Highly durable. Quick drying and easy to apply.

Colour range	PBW and 420 light fast optimised tinted colours from the Weathershield fandeck as well as a range of NCS2, RAL and BS colours
Pack sizes	5L
Touch dry	Mid sheen
Touch dry	2-4 hours
Recoatable	4-6 hours
Coverage	Up to 17m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- Excellent finish
- High opacity
- Excellent adhesion

Pyroshield Basecoat

A flame-retardant basecoat to be used as part of a system for upgrading the reaction to fire surface classification

Water-Based

DATA SHEET 450



Key Benefits

Upgrades the Class 4 Warrington Blue Board to Class 1 and Class O. For use over multi-layered paint systems.

Colour range	White
Pack sizes	10L
Touch dry	2 hours
Recoatable	12 hours
Coverage	3 coats of Pyroshield are normally required to achieve a combined coverage of 0.46m ² per litre. Pyroshield Basecoat should be applied by roller to achieve a coverage of 1.4m ² per litre, per coat. A 10L container of Pyroshield Basecoat from Dulux Trade should cover no more than 14m ²
Thinning	This product should not be thinned, but must be stirred thoroughly in the can before use

- No antimony or brominated compounds. Water-based, quick drying formulation
- The thick film gives a slightly textured finish, which may be modified with appropriate texturing tools
- Overcoat **Pyroshield** Basecoat with an approved **Dulux Trade** decorative finish

Pyroshield Durable Matt

A durable matt flame retardant for upgrading the reaction to fire service classification for moderate risk surfaces

Water-Based

DATA SHEET 539



Key Benefits

Inhibits the spread of flame on previously painted walls and ceiling surfaces in the event of a fire.

Colour range	White and approximately 3000 tinted colours
Pack sizes	5L
Touch dry	2-4 hours
Recoatable	2-4 hours
Coverage	2 coats of Pyroshield Durable Matt are required at a coverage of 12m ² per litre
Thinning	This product must not be thinned

- No antimony or brominated compounds
- Water-based, quick drying formulation
- Suitable for all plaster based interior wall and ceiling surfaces
- The thin film gives a smooth finish

Pyroshield Durable Eggshell

A water-based flame retardant finish that upgrades surfaces of fire classification from Class 3 to Class 0 (BS476)

Water-Based

DATA SHEET 546



Key Benefits

Inhibits the spread of flame on previously painted walls and ceiling surfaces. It is a durable eggshell that is tintable in a wide range of colours.

Colour range	Available in a range of tinted colours
Pack sizes	5L
Touch dry	Dependent upon temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 12m ² per litre
Thinning	Please refer to data sheet for details

- Quick drying water-based formulation that is both durable and washable
- Proven to upgrade Class 3 substrates to Class 0
- Only 2 coats required to achieve a smooth, attractive finish
- Suitable for interior use and is designed to maintain or improve flame retardancy of new or previously painted plasterboard, plaster, cement render, blockwork etc. walls and ceilings

Specialist Products

Metalshield Gloss Finish

A high performance metal coating finish

Solvent-Based

DATA SHEET 512



Key Benefits

Up to 8 years rust protection for metal when applied with the appropriate **Metalshield** primer.

Colour range White, Black, Silver, Gold and over 1,500 colours

Pack sizes 1L, 2.5L, 5L

Touch dry 1-2 hours

Recoatable 4-6 hours

Coverage Up to 13m² per litre

Thinning Thinning not generally required

- Increases maintenance cycles when used as part of the **Dulux Trade Metalshield** system (saves money)
- Quick drying times
- Attractive gloss finish
- Wide choice of colours
- Suitable for railings, garage doors, lift shafts, staircases and emergency exit routes

Metalshield Satin Finish

A high performance metal coating finish

Solvent-Based

DATA SHEET 541



Key Benefits

Up to 8 years protection for metal when applied with the appropriate **Metalshield** primer.

Colour range White, Black and over 1,500 colours

Pack sizes 2.5L, 5L

Touch dry 1-2 hours

Recoatable 4-6 hours

Coverage Up to 13m² per litre

Thinning Thinning not generally required

- Increases maintenance cycles when used as part of the **Dulux Trade Metalshield** system (saves money)
- Quick drying times
- Attractive satin finish
- Wide choice of colours
- Suitable for railings, garage doors, lift shafts, staircases and emergency exit routes

Floorshield

A hard-wearing floor paint ideal for use in domestic, commercial and light industrial environments

Solvent-Based

DATA SHEET 507



Key Benefits

Excellent film hardness and abrasion resistance. Single pack formulation.

Colour range	Ash Grey and over 1,500 colours
Pack sizes	5L
Touch dry	2-4 hours
Recoatable	12-16 hours
Coverage	Up to 16m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

- Withstands repeated washing and mild chemical spillage
- Formulated for use on concrete, wood and steel
- Suitable for many applications: walkways, warehouses, factories and catering facilities

Dulux Trade High Performance Floor Paint

A two pack water-based epoxy floor paint suitable for areas of high wear and commercial usage

Water-Based

DATA SHEET 533



Key Benefits

A highly durable finish suitable for use in heavy commercial environments.

Colour range	Goosewing and Tideway
Pack sizes	5L when mixed (1.78L Base and 3.22L Activator)
Finishes	Mid sheen
Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 6m ² per litre
Thinning	This product can be thinned. Please refer to data sheet for details

Tip: Supplied in correct proportions. Add all of the Base to the Activator container and mix thoroughly for at least 5 minutes, until the product is smooth and even.

Specialist Products

Dulux Trade Anti Graffiti Sealer

Part 1 of a complete 3 part system. For use on bare concrete or eroded surfaces before application of primer and finish

Water-Based

DATA SHEET 812



Key Benefits

Withstands frequent cleaning, maintaining a decorative finish for longer.

Colour range	White
Pack sizes	5L when mixed (4.175L and 0.825L)
Finish	Matt
Touch dry	4-6 hours
Recoatable	Minimum 16 hours, maximum 7 days. Hard dry after 16 hours
Pot life	8 hours at 20°C

- Use as part of the anti-graffiti system
- For use on areas exposed to repeated graffiti
- Delivers a more pleasant built environment

Tip: This range can be used either where graffiti is a problem or as hygienic coating. e.g. hospitals, industrial kitchens and food & drink processing industries.

Dulux Trade Anti Graffiti Primer

Part 2 of a complete 3 part system. For use on sound previously painted surfaces or after sealed bare concrete

Water-Based

DATA SHEET 813



Key Benefits

Withstands frequent cleaning, maintaining a decorative finish for longer.

Colour range	White
Pack sizes	5L when mixed (4L Base and 1L Activator)
Finish	Matt
Touch dry	4-6 hours at 20°C
Recoatable	Minimum 16 hours, maximum 7 days. Hard dry after 16 hours
Pot life	6 hours at 20°C

- Use as part of the anti-graffiti system
- For use on areas exposed to repeated graffiti
- Delivers a more pleasant built environment

Dulux Trade Anti Graffiti Finish

Part 3 of a complete 3 part system. For use after primer on both previously painted and new surfaces

Water-Based

DATA SHEET 814



Key Benefits

Withstands frequent cleaning, maintaining a decorative finish for longer.

Colour range	72 pastel colours
Pack sizes	5L when mixed (4.13L Base and 0.87L Activator)
Finish	Gloss
Touch dry	6 hours at 20°C
Recoatable	Minimum 16 hours, maximum 7 days. Hard dry after 16 hours
Pot life	6 hours at 20°C
Coverage	Up to 10m ² per litre
Application	A brush should be only used for "cutting-in". When using a brush, allow 1 hour before overcoating
Thinning	Thinning not generally required. Please refer to data sheet for details

- Tough, durable and cost effective solution to graffiti vandalism
- Alternative solution for hygiene sensitive areas

Dulux Trade Line Marking Paint

A hard-wearing, single pack, acrylated rubber line marking paint for interior and exterior use

Solvent-Based

DATA SHEET 525



Key Benefits

Single pack formulation. Excellent adhesion and durability. Withstands repeated washing and mild chemical spillage.

Colour range	White, yellow
Pack sizes	5L
Touch dry	30 minutes
Recoatable	1 hour
Coverage	Up to 10m ² per litre
Thinning	This product should not be thinned

- Attractive high build finish
- Excellent scuff resistance

Specialist Products

Mouldshield Fungicidal Matt^{##}

A matt emulsion paint that contains a mild fungicide

Water-Based

DATA SHEET 412



Key Benefits

Fungicide inhibits mould on paint surface. Excellent adhesion and opacity.

Colour range	PBW and over 14,000 colours, including many Colour Palette , NCS2 and BS colours
Pack sizes	5L
Touch dry	Dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 17m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- Ideal for use on woodchip, blown vinyl wall coverings etc., as well as dry plaster and a range of building boards
- For use on interior walls and ceilings where surface mould growths are a problem

^{##}see back page for details

Mouldshield Fungicidal Eggshell^{##}

Ideal for kitchens and bathrooms

Water-Based

DATA SHEET 409



Key Benefits

Fungicide inhibits mould on paint surface. Excellent adhesion.

Colour range	PBW and more than 7,000 colours, including many Colour Palette , NCS2 and BS colours
Pack sizes	5L
Touch dry	Dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	This product can be thinned. Please refer to data sheet for details

- More resistant to condensation than conventional emulsion paints
- For use on interior walls, ceilings and woodwork, where surface mould growth is a problem

^{##}see back page for details

Dulux Trade Cellar Paint

A unique NAD (Non-Aqueous Dispersion) formulation

Solvent-Based

DATA SHEET 503



Key Benefits

Fungicide inhibits mould growth on paint surface.

Colour range	PBW
Pack sizes	5L
Touch dry	1-5 hours
Recoatable	After 2-16 hours. The drying time will vary according to temperature and humidity, e.g. the drying times quoted will be significantly longer in cold, damp conditions
Coverage	Up to 16m ² per litre on sealed surfaces
Thinning	Thinning not generally required. Please refer to data sheet for details

- Can be applied to interior masonry surfaces (not common or fletton brickwork) that are slightly damp but not saturated, such as cellars, porches and conservatories

Pre-decorative Products

Polycell Trade is a comprehensive range of trade formulated pre-decorative products, created to help professionals get the sure foundation you need for high quality paint and wallpaper finishes, as well as being practically designed for everyday use.

Pre-decorative Products

	Place of application		
	Level of Damage to Surface		
	Minor Imperfections (Interior Only)	Medium Sized Imperfections	
Interior		Exterior	
Polyfilla Interior Filler		✓	
Polyfilla Exterior Filler			✓
Polyfilla All Purpose		✓	✓
Polyfilla Deep Hole			
Polyfilla One Fill			
Polyfilla Fine Surface	✓		
Polyfilla Quick Drying Filler	✓		
Polyfilla Woodflex		✓	✓
Polyfilla Decorators Caulk		✓	✓
Polyfilla Expanding Foam			
Polycell Stain Block			



		Problem Areas	Paintable	Composition
Large or Deep Imperfections		Stained Surfaces		
Interior	Exterior			
			Up to 24 hours	Powder
			Up to 24 hours	Powder
			Up to 24 hours	Powder/ Ready Mixed
✓	✓		30 minutes	Ready Mixed
✓	✓		From 15 minutes	Ready Mixed
			1 hour	Ready Mixed
			10 minutes	Ready Mixed
			Up to 24 hours	Ready Mixed
			1 hour	Ready Mixed
✓	✓		4 hours	Ready Mixed
		✓	10 mins/ 12 hours	Solvent-based

Pre-decorative

Polyfilla Interior Filler

For indoor repairs to plaster, plasterboard, wood, brick, stone and most other building materials

Powder

DATA SHEET 119/120



Key Benefits

Won't shrink or crack. Easy to sand to a very smooth finish.

Pack sizes	2kg, 5kg, 10kg
Paintable	Up to 24 hours
Set time	1 hour depending on surface, temperature, relative humidity and depth of fill
Working time	50 minutes
Mix ratio	2 to 2.5 parts filler to 1 part water

- Ideal for painting because it's resistant to flashing and grinning
- Accepts nails and screws

Polyfilla Exterior Filler

Based on high strength cement and special resins to promote powerful adhesion, toughness and impact resistance

Powder

DATA SHEET 115



Key Benefits

Rock hard finish, good impact resistance.

Pack sizes	2kg
Paintable	Up to 24 hours
Set time	1 hour depending on surface, temperature, relative humidity and depth of fill
Working time	30 minutes
Mix ratio	4.5 parts of filler to 1 part water

- Strong adhesion, accepts fixings, nails and screws
- Always use an alkali-resistant primer before application
- Easy to sand

Polyfilla All Purpose

For indoor and outdoor repairs to most building materials

Powder &
Ready-Mixed

DATA SHEET 112/113



Key Benefits

Smooth, easy to sand. Dries white, will not shrink or crack.

Pack sizes	Ready-Mixed: 1kg, 2kg Powder: 2kg, 5kg, 10kg
Paintable	Up to 24 hours depending on surface, temperature, relative humidity and depth of fill. Ready Mixed 1cm layers will be surface dry in about 1 hour
Set time	Up to 4 hours depending on surface, temperature, relative humidity and depth of fill

- Accepts nails and screws
- Strong adhesion

Polyfilla Deep Hole

Fills holes up to 50mm deep in one application and is ready to paint from 30 minutes

Ready-Mixed

DATA SHEET 129/130



Key Benefits

A structural filler for deep holes. No shrinking, cracking or sagging.

Pack sizes	2 x 500g
Paintable	From 30 minutes
Mix ratio	1:1, 2 part pack

- Accepts screws and nails
- Smooth finish
- Ultimate ease of sanding
- Interior and exterior use

Pre-decorative

Polyfilla One Fill

A lightweight filler designed to fill deep repairs in one application without sagging or slumping - even on ceilings

Ready-Mixed

DATA SHEET 121



Key Benefits

Smooth finish - no need to sand.

Pack sizes 600ml, 1L, 4L

Paintable 15 minutes depending on surface, temperature, relative humidity and depth of fill

- Millions of microscopic glass beads give no-sag characteristics
- Will not shrink or crack
- Not structural
- For interior and exterior use

Polyfilla Fine Surface

For filling minor cracks, surface imperfections and open woodgrain on interior surfaces

Ready-Mixed

DATA SHEET 116



Key Benefits

Extra adhesive strength grips the surface and allows fine feathering.

Pack sizes 500g, 1.75kg

Paintable 30 to 60 minutes depending on surface and surrounding conditions

- Sands to a glass-smooth finish
- No need to prime - over-paint in an hour

Polyfilla Quick Drying Filler

For small interior jobs when you're in a hurry

Ready-Mixed

DATA SHEET 122



Key Benefits

Can be used straight from the tube. Ideal for small interior jobs when you are in a hurry.

Pack sizes 330g

Paintable Set in as little as 10 minutes

- Sands easily
- Will not shrink or crack
- Fills hairline cracks

Polyfilla Woodflex

Flexible, water-resistant filler that bonds strongly to wood

Ready-Mixed

DATA SHEET 124/125



Key Benefits

Can be painted or stained. Interior and exterior use.

Pack sizes 330g tube, 600ml tub

Paintable Up to 24 hours depending on surface, temperature, relative humidity and depth of fill. 1cm thick layers will be surface dry in about 2 hours

- Dries to a smooth and flexible finish
- Water-resistant finish will not shrink or crack
- Easy to use and sand
- Specially formulated to fill holes of any depth or size

Pre-decorative

Polyfilla Decorators Caulk

Water resistant, flexible acrylic sealant for interior and exterior applications

Ready-Mixed

DATA SHEET 103/104/131



Key Benefits

Smooth finish - no need to sand

Pack sizes	290ml (white only) and 380ml (all colours)
Paintable	1 hour depending on surface, temperature, relative humidity and depth of fill

- Available in White, Magnolia and Brown

Polyfilla Expanding Foam

Expands to fill large holes and gaps, inside and outside

Ready-Mixed

DATA SHEET 114/132



Key Benefits

Expands up to 45 times can volume. Easy to cut, sand, paint and plaster. Strong, long-lasting, damp-resistant seal.

Pack sizes	500ml
Paintable	Can be cut after 30 minutes and sanded, plastered or painted after 3-4 hours

- Will not shrink when cured

Polycell Stain Block

Permanently blocks most problem stains and prevents bleeding through after decoration

Solvent-Based

DATA SHEET 107/108



Key Benefits

The aerosol can be overpainted in about 10 minutes. Treats stains caused by water, nicotine, soot, graffiti, grease, wax and rust.

Pack sizes	500ml, 1L, 2.5L
Touch dry	2-3 hours
Paintable	Liquid: 12 hours. Aerosol: 10 minutes
Coverage	Liquid: 7.9m ² per litre. Aerosol: 0.8m ² per 250ml

- Available as conventional paint or aerosol
- For interior use

Polycell Extra Strong Paste

Instantly mixes to a smooth paste offering easy slippage and excellent wet tack

Flakes

DATA SHEET 106



Key Benefits

Instant mix to smooth paste. Long working time, easy slip, excellent wet tack. Extra strong adhesion. Low salt content means improved stain prevention.

Pack sizes	10 and 30 rolls
Coverage	Normal = 8-10 rolls per satchet. Heavy = 3-4 rolls per satchet
Drying time	14-18 hours

- To get the best results make sure surfaces are clean, dry and free from powdery material and mould
- For interior use

Pre-decorative

Polycell Ready Mixed Adhesive

Low water content makes it ideal for wallcoverings prone to shrinkage. Easy to use straight from the tub

Ready-Mixed

DATA SHEET 128



Key Benefits

Easy to use straight from the tub. High initial wet tack resulting in strong final adhesion.

Pack sizes	4.5kg
Coverage	1 roll per kg
Drying time	14-18 hours

- Excellent slip, long open time
- Low water content means ideal for wallcoverings prone to shrinkage
- To get the best results make sure the surfaces to be papered are sound, clean and dry. (New surfaces particularly must be fully dry)
- For interior use

From the **best** known
name in paints...



...providing great
results, whatever
the job at hand

Professional quality you
can trust from a name you
already do

Visit www.polycelltrade.co.uk
or call 08444 817 818



Woodcare

To protect internal and external wood for the long term, **Dulux Trade** offers a wide range of professional woodcare products. Formulated for exceptional performance, each has been developed to deliver outstanding results for any job.

Exterior Products

	Place of application		
	Doors	Joinery	Facias/Cladding
Weathershield Ultimate Woodstain	✓	✓	✓
Weathershield Ultimate Opaque	✓	✓	✓
Weathershield Aquatech Woodstain	✓	✓	✓
Weathershield Aquatech Opaque	✓	✓	✓
Weathershield Aquatech Preservative Basecoat+ ^{(BP)†}	✓	✓	✓
Protective Woodsheen	✓	✓	✓
Classic Select Woodstain			✓
Weathershield Yacht Varnish	✓		

Interior Products

	Place of application		
	Doors	Floors	Furniture
Protective Woodsheen	✓		✓
Danish Oil			✓
Diamond Glaze	✓	✓	✓
Polyurethane Varnish	✓	✓	✓
Quick Drying Varnish	✓		✓

[†]See back cover for full details.



Product Finish			Water/ Solvent- based
Semi-Transparent	Clear	Opaque	
✓			Solvent-based
		✓	Solvent-based
✓			Water-based
		✓	Water-based
✓			Water-based
✓			Solvent-based
✓			Solvent-based
	✓		Solvent-based

Trim	Joinery	Product Finish		Water/ Solvent- based
		Semi-Transparent	Clear	
✓	✓	✓		Solvent-based
	✓		✓	Solvent-based
✓	✓	✓	✓	Water-based
✓	✓		✓	Solvent-based
✓	✓	✓	✓	Water-based

Woodcare

Weathershield Ultimate Woodstain

A high performance semi-transparent woodstain, ideal for exterior joinery and cladding

Solvent-Based

DATA SHEET 623



Key Benefits

Exceptional durability – up to 10 years weather protection. Highly flexible finish resists cracking, flaking and peeling.

Colour range	Available in 21 natural wood colours
Pack sizes	1L, 2.5L, 5L
Touch dry	4-6 hours
Recoatable	16 hours
Coverage	Smooth wood: up to 20m ² /litre/coat (normally 2 coats)

- Excellent water repellency
- Traditional application properties
- For new wood, use with **Weathershield Aquatech Preservative Basecoat+** ^{(BP)†}

†See back cover for full details.

Weathershield Ultimate Opaque

Ideal for exterior joinery and cladding

Solvent-Based

DATA SHEET 624



Key Benefits

Exceptional durability – up to 10 years weather protection. Highly flexible opaque finish resists cracking, flaking and peeling.

Colour range	Available in 600 colours within the opaque range
Pack sizes	1L, 2.5L, 5L
Touch dry	4-6 hours
Recoatable	16 hours
Coverage	Smooth wood: up to 20m ² /litre/coat (normally 2 coats)

- Excellent water repellency
- For new wood, use with **Weathershield Aquatech Preservative Basecoat+** ^{(BP)†}

†See back cover for full details.

Weathershield Aquatech Woodstain

A quick drying, high performance semi-transparent woodstain, ideal for exterior joinery and cladding

Water-Based

DATA SHEET 615



Key Benefits

Exceptional durability – up to 6 years weather protection. Highly flexible finish resists cracking, flaking and peeling. Quick drying - recoatable in 2 hours.

Colour range	Available in 21 natural wood colours
Pack sizes	1L, 2.5L, 5L
Touch dry	1 hour
Recoatable	2 hours
Coverage	Smooth wood: up to 20m ² /litre/coat (normally 2 coats)

- For new wood, use with **Weathershield Aquatech Preservative Basecoat+ (EP)[†]**

[†]See back cover for full details.

Weathershield Aquatech Opaque

A quick drying water-based opaque finish, ideal for exterior joinery and cladding

Water-Based

DATA SHEET 611



Key Benefits

Exceptional durability – up to 6 years weather protection. Highly flexible opaque finish resists cracking, flaking and peeling. Quick drying - recoatable in 2 hours.

Colour range	Available in 600 colours within the opaque range
Pack sizes	1L, 2.5L, 5L
Touch dry	1 hour
Recoatable	2 hours
Coverage	Smooth wood: up to 20m ² /litre/coat (normally 2 coats)

- For new wood, use with **Weathershield Aquatech Preservative Basecoat+ (EP)[†]**

[†]See back cover for full details.

Weathershield Aquatech Preservative Basecoat^{+(BP)[†]}

A quick drying water-based preservative basecoat,
ideal for use on bare wood

Water-Based

DATA SHEET 614



Key Benefits

Preserves, penetrates and seals. Protects against blue stain, rot and UV rays.

Pack sizes	1L, 2.5L
Touch dry	2 hours dependent on temperature and humidity
Recoatable	Up to 24 hours
Coverage	Smooth wood: 4-5m ² /litre/coat (2 even coats)

[†]See back cover for full details.



Dulux Trade Classic Select Woodstain

A low build, matt, semi-transparent woodstain ideal for large areas such as cladding, fascias and soffits

Solvent-Based

DATA SHEET 609



Key Benefits

Offers up to 4 years exterior weather protection. Deep penetrating woodstain which will not blister or flake.

Colour range	Available in 21 natural wood and 18 designer colours
Pack sizes	1L, 2.5L, 5L*
Touch dry	4-6 hours
Recoatable	16 hours
Coverage	Smooth wood: up to 14m ² /litre/coat (normally 2 coats). Rough sawn wood: up to 8m ² /litre/coat

- Suitable for smooth planed wood and rough sawn timber
- For new wood, use with **Weathershield Aquatech** Preservative Basecoat+ ^{(EP)†}

*Not all colours available in all pack sizes.

†See back cover for full details.

Weathershield Yacht Varnish

A durable, solvent-based clear varnish ideal for hardwood doors

Solvent-Based

DATA SHEET 608



Key Benefits

Up to 3 years weather protection. Durable and flexible film which resists flaking and peeling. Contains UV filters which protect against strong sunlight.

Colour range	Clear gloss
Pack sizes	1L, 2.5L
Touch dry	6-8 hours
Recoatable	16-24 hours
Coverage	Smooth wood: up to 16m ² /litre/coat (normally 2-3 coats on new/bare wood)

- For new wood, use with **Weathershield Aquatech** Preservative Basecoat+ ^{(EP)†}

†See back cover for full details.

Dulux Trade Protective Woodsheen

A semi-transparent woodstain, ideal for interior and exterior joinery

Solvent-Based

DATA SHEET 605



Key Benefits

Offers up to 4 years exterior weather protection. Flexes with the wood to resist cracking, flaking and peeling.

Colour range	Available in 21 natural wood and 18 designer colours
Pack sizes	1L, 2.5L, 5L, 20L
Touch dry	4-6 hours
Recoatable	14-16 hours
Coverage	Smooth wood: up to 20m ² /litre/coat (normally 2 coats)

- Suitable for hardwoods and softwoods
- For exterior new wood, use with **Weathershield Aquatech Preservative Basecoat+** (BP)†
- Can also be used as an interior product

†See back cover for full details.

Dulux Trade Danish Oil

A natural oil that permeates the wood surface, ideal for interior and exterior furniture and joinery

Solvent-Based

DATA SHEET 620



Key Benefits

Water-resistant, clear matt finish. Suitable for both internal and external hardwoods and softwoods.

Colour range	Clear
Pack sizes	1L, 2.5L
Touch dry	2-4 hours
Recoatable	Min. 6 hours
Coverage	Up to 6m ² /litre depending on porosity of the wood

- Application with brush or cloth

Dulux Trade Diamond Glaze

A water-based lacquer for maximum durability, ideal for floors, doors, trim, furniture and joinery

Water-Based

DATA SHEET 616



Key Benefits

Up to 10 times tougher than conventional varnish*.
Quick drying.

Colour range	Available in 21 natural wood and 18 designer colours
Pack sizes	1L, 2.5L, 5L
Touch dry	1-2 hours
Recoatable	2-4 hours
Coverage	Smooth wood: up to 25m ² /litre/coat (normally 2-3 coats on new/bare wood)

- For all high wear interior wood surfaces, especially floors

*10 times tougher than conventional varnish, based on hardness tests undertaken with the use of Research Equipment London (REL) testing equipment.



Dulux Trade Polyurethane Varnish

A high-build interior varnish, ideal for doors, trim, furniture, joinery and floors#

Solvent-Based

DATA SHEET 607



Key Benefits

Translucent solvent-based finish. Withstands knocks, scuffs and spills.

Colour range	Clear gloss, matt and satin finishes
Pack sizes	1L, 2.5L, 5L
Touch dry	6-8 hours
Recoatable	16-24 hours
Coverage	Smooth wood: up to 16m ² /litre/coat (normally 1-2 coats)

- Can be used on bare or previously varnished surfaces or over wood dye

#Light wear only

Dulux Trade Quick Drying Varnish

A quick drying interior varnish, ideal for doors, trim, furniture and joinery

Water-Based

DATA SHEET 604



Key Benefits

Contains Polyurethane. Can be used on bare or previously varnished surfaces, or over wood dye. Quick drying.

Colour range	Clear gloss and satin finish. Also available in 21 natural wood and 18 designer colours
Pack sizes	1L, 2.5L
Touch dry	30 minutes
Recoatable	2 hours
Coverage	Smooth wood: up to 20m ² /litre/coat (normally 2-3 coats on new/bare wood)

- Can be used on bare or previously varnished surfaces or over wood dye

**“On woodstains,
I wouldn’t use
anything else to
be quite honest.”**

*Trusted by Brian Morton,
Professional Decorator*





Dulux TRADE **paint** **EXPERT**

Get the latest trade talk, tips and true stories

Download the **FREE** App or visit
www.duluxtradepaintexpert.co.uk

- Product selection – information at your fingertips
- 'How to' videos
- The latest products
- Stories from fellow tradesmen
- Trade news and hot topics
- Win great prizes
- Find your nearest stockist



**Share your best work and see
what everyone's up to**

Send us your pictures and check out the
'Jobs in Progress' section.



[facebook.com/
duluxtradepaintexpert](https://facebook.com/duluxtradepaintexpert)



[twitter.com/
dtpaintexpert](https://twitter.com/dtpaintexpert)



[youtube.com/
duluxtradeuk](https://youtube.com/duluxtradeuk)



FREE iPhone app

Grab it from the Apple App store and tap into all this and more.

Powered by



Dulux Trade Website



On our website

www.duluxtrade.co.uk you will

find all the accurate, up-to-date information that decorators need. Whether you want to ask us about colour availability or have a specific question about a particular finish, you'll find all the answers you're looking for online.

Plus, by registering your details at the site you can also choose to receive regular updates on everything that's new in the **Dulux Trade** range, from the latest products to current promotions.

- Full product information, including data sheets
- Browse products by purpose, range and colour
- Order A8 colour samples and colour cards
- Download and order product literature
- News and case studies
- Useful videos
- Register for regular product updates



Like our products on Facebook and tweet about our products on Twitter.



facebook.com/duluxtrade



twitter.com/duluxtrade



youtube.com/duluxtrade.co.uk



Trust Dulux to help develop your business

You'll be able to offer customers the ultimate peace of mind in the shape of a two year guarantee with your workmanship underwritten by **Dulux** – one of the most trusted names in decorating.

We've listed a few benefits below...

A big brand behind you – association with the world's leading paint manufacturer – **AkzoNobel**



Dulux will underwrite your workmanship for 2 years** **GUARANTEED**

Unique web profile on **www.dulux.co.uk**, so customers searching for a decorator can view your details



Access to free advertising material and professional business templates



Dedicated homeowner line for customers seeking a local **Dulux Select Decorator**



Free training for you and your employees#



AXA ICAS helpline service – a free, 24 hour legal, financial and personal support service available 365 days a year



Advertising the **Dulux Select Decorators** scheme through 8 million colour cards



**Terms and conditions apply

#See back page for full details

“The Dulux Select Decorators scheme is second to none”

Trusted by Wendy Macklin, Dulux Select Decorator of the year Grand Winner 2012



Want to become a Dulux Select Decorator?



Have you worked as a painter and decorator for 3 years?



Have you run your own business for at least 1 year?



Can you provide 3 customer references from completed jobs?



Are you confident of passing a full on-site assessment of your workmanship and customer service?

If you don't meet the criteria above, you may still be eligible to become an Associate member. Please contact the **Dulux Select Decorators** office.

Full membership	£195.00 (excluding VAT) ^{††}
Associate membership	£130.00 (excluding VAT) ^{††}

For more information call 08444 817 846
or visit: www.duluxselectdecorators.co.uk

^{††}See back page for full details

Dulux Trade Contractor Partnership



Dulux Trade Contract Partnership is an exclusive membership scheme of independently assessed, quality assured painting contractors.

By joining the scheme, contractors are demonstrating their commitment to providing an outstanding professional service to their clients.

A Dulux Trade Contract Partner is committed to:

- Quality workmanship
- Delivering a professional service
- Continual improvement
- Providing value for money
- Being reliable and trustworthy
- Meeting your sustainability goals

The on-going assessment programme and Code of Practice demonstrate how **Dulux Trade Contract Partners** are working to a consistently high standard of workmanship and professionalism.

When you need a project completed right first time, on time and there is no room for error – you can rely on a **Dulux Trade Contract Partner**. For more information visit: www.contractpartnership.co.uk



All you need to know, just a click away

World-famous specialist brands including **Sikkens** and **Polycell Trade** are part of the same family as **Dulux Trade**. So, whether you are looking for the perfect product to achieve the most professional finish possible, or making sure you get the preparation just right, there's an **AkzoNobel** applicator guide to help.

Polycell Trade professional product guide

Your complete guide to the comprehensive range of fillers, adhesives and painting aids made for the trade.

Dulux Trade Weathershield applicator guide

Makes choosing and using the unbeatable collection of finishes that enhance exterior masonry and trim easy. Provides outstanding weather protection for up to 15 years.

Dulux Trade Diamond range applicator guide

The superior range of water-based interior finishes that are up to 10x tougher than vinyl silk – making sure those good looks last long into the future.

Dulux Trade Ecosure range

Making the most of the **Dulux Trade** range of water-based paints developed to deliver optimum sustainability with no compromise on performance.

Dulux Trade, Cuprinol Trade and Sikkens woodcare applicator guides

Whether treating, preserving or transforming interior, exterior or landscape wood, these guides cover all your woodcare needs.



Visit www.duluxtrade.co.uk to download and order these guides online.

Quick reference guide

Alkali Resisting Primer.....	17
All Purpose Primer.....	16
Aluminium Wood Primer.....	13
Anti-Graffiti Finish.....	55
Anti-Graffiti Primer.....	54
Anti-Graffiti Sealer.....	54
Blockfiller Plus.....	49
Cellar Paint.....	57
Cladshield.....	50
Classic Select Woodstain.....	73
Danish Oil.....	74
Diamond Eggshell.....	26
Diamond Eggshell, Light & Space.....	26
Diamond Glaze.....	75
Diamond High Performance.....	26
Diamond Matt.....	25
Diamond Matt, Light & Space.....	25
Diamond Satinwood.....	33
Dry Fall Eggshell.....	49
Durable Flat Matt.....	25
Durable Flat Matt, Light & Space.....	25
Ecosure Gloss.....	30
Ecosure Matt.....	22
Ecosure Matt, Light & Space.....	22
Ecosure Quick Drying Eggshell.....	27
Ecosure Undercoat.....	30
Eggshell.....	34
Fast Matt.....	23
Floorshield.....	53
High Gloss.....	31
High Performance Floor Paint.....	53
Line Marking Paint.....	55
Metal Primer.....	15
Metalshield Gloss Finish.....	52
Metalshield Quick Drying Metal Primer.....	14
Metalshield Satin Finish.....	52
Metalshield Zinc Phosphate Primer.....	14
Mordant Solution.....	15
Mouldshield Fungicidal Eggshell.....	56
Mouldshield Fungicidal Matt.....	56
New Work Gloss.....	32
New Work Undercoat.....	32
Polycell Extra Strong Paste.....	65
Polycell Ready Mixed Adhesive.....	66
Polycell Stain Block.....	65
Polyfilla All Purpose.....	61
Polyfilla Decorators Caulk.....	64
Polyfilla Deep Hole.....	61
Polyfilla Expanding Foam.....	64

Polyfilla Exterior Filler.....	60
Polyfilla Fine Surface.....	62
Polyfilla Interior Filler.....	60
Polyfilla One Fill.....	62
Polyfilla Quick Drying Filler	63
Polyfilla Woodflex.....	63
Polyurethane Varnish.....	76
Primer Sealer.....	16
Protective Woodsheen	74
Pyroshield Basecoat.....	50
Pyroshield Durable Eggshell.....	51
Pyroshield Durable Matt.....	51
Quick Drying MDF Primer Undercoat.....	13
Quick Drying Varnish	76
Quick Drying Wood Primer Undercoat	12
Satinwood.....	33
Stain Block Plus	17
Sterishield Diamond Matt.....	48
Sterishield Quick Drying Eggshell.....	48
Super Grip Primer.....	18
Supermatt	23
Ultra Grip Primer.....	18
Undercoat	31
Vinyl Matt.....	22
Vinyl Matt, Light & Space.....	22
Vinyl Silk	24
Vinyl Soft Sheen	24
Weathershield All Seasons Masonry Gloss.....	40
Weathershield All Seasons Masonry Paint.....	39
Weathershield Aquatech Opaque	71
Weathershield Aquatech Preservative Basecoat+	72
Weathershield Aquatech Woodstain	71
Weathershield Exterior Flexible Filler.....	44
Weathershield Exterior Flexible Undercoat	42
Weathershield Exterior High Gloss.....	43
Weathershield Maximum Exposure Smooth Masonry Paint	39
Weathershield Multi-Surface Fungicidal Wash.....	44
Weathershield Preservative Primer+.....	42
Weathershield Quick Drying Exterior Gloss	41
Weathershield Quick Drying Exterior Undercoat.....	40
Weathershield Quick Drying Satin	41
Weathershield Smooth Masonry Paint	38
Weathershield Stabilising Primer	43
Weathershield Textured Masonry Paint.....	38
Weathershield Ultimate Opaque.....	70
Weathershield Ultimate Woodstain	70
Weathershield Yacht Varnish	73
Wood Primer	12

Contact Us

To receive more information on **Dulux Trade** products register online at www.duluxtrade.co.uk

You can also request information, technical advice and help with product specification by calling **08444 817 818**
Email: duluxtrade.advice@akzonobel.com

Or write to: **Trade Technical Advice Centre, ICI Paints AkzoNobel, Wexham Road, Slough SL2 5DS**

Interact with Dulux Trade



#Courses are free for members of the Dulux Select Decorators scheme to attend, for other painters and decorators a fee may apply, please see website for details. Specialist courses will also be made available and fees will apply.

**Fees can be paid annually or in monthly instalments. Prices are correct at time of publication, this is subject to change. Monthly direct debits are subject to an administration fee.

*This figure is based on theoretical calculations on pairs of bare rooms of dimensions 4 x 3 x 2.4m where the light incident on all surfaces is averaged. The rooms all have the same mid-grey floor colour (LRV 50). They have a white ceiling and a colour on the walls. In one of each pair, the colour used is from the Light & Space range. In the other, the colour used is from conventional products. The Light & Space and conventional colours have similar hue (colour family) and chroma (intensity of colour). The energy savings will not always equate to 22%. They will vary depending on the contents, dimensions and floor colour of the room and will differ if lighting in particular areas needs to be controlled. The calculated figure varies from 14% to 28% depending on the wall colour chosen. The actual light energy savings achieved in practice may differ from the calculations.

◇Compared with Dulux Trade Vinyl Matt 2011 formulation.

**Whilst leading-edge technology has been used in the development of this product, the nature of solvent-based paints means that they will discolour over time. The rate of discolouration is faster in areas with no or low natural or UV light.

**Dulux Trade Mouldshield Fungicidal Eggshell and Dulux Trade Mouldshield Fungicidal Matt contain 3-iodo-2-propynyl-n-butylcarbanate. †Dulux Trade Weathershield Aquatech Preservative Basecoat+ (BP) and Dulux Trade Weathershield Preservative Primer+ (BP) contain propiconazole and IPBC. USE BIOCIDES SAFELY. ALWAYS READ THE LABEL AND PRODUCT INFORMATION BEFORE USE.

AkzoNobel, the AkzoNobel logo, ICI, the ICI roundel, Dulux, Dulux Trade, Trade & Trusted, Dulux Select Decorators, Ecosure, Weathershield, Weathershield All Seasons, Heritage, Aquatech, Polycell, Polcell Trade, Polyfilla, Woodflex Polyfilla, Metalshield, Sterishield, Dulux Dry Fall, Cladshield, Pyroshield, Floorshield, Diamond Glaze, Cuprinol, Cuprinol Trade, Sikken, Light & Space, Lumitec, Colour Palette and the Dulux Trade Paint Expert logo are trade marks of the AkzoNobel group. © AkzoNobel 2013.

Glidden is a registered trade mark of PPG Architectural Finishes, Inc