

# Cantana Duet

## Product description



Antismudsbehandlet  
Antisoiling protected  
Schmutzabweisend  
Traitée antissalissure



**ege**<sup>®</sup>  
design · quality · respect

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
<b>Construction</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% Polypropylen
Coloration	-	Solution dyed
Backing	eTL	HL - High foam
Dimensions	ISO 3018	Ca. 400/500 cm
Total thickness	ISO 1765	Ca. 9,5 mm.
Surface pile thickness	ISO 1766	Ca. 4,0 mm.
Tufts	ISO 1763	Ca. 71.000 pr.m2
Total carpet weight	ISO 8543	Ca. 3.100 g/m2
Pile yarn weight	eTL	775 g/m2
Surface pile density	ISO 8543	Ca. 0,125 g/cm3
ege soil protection	eTL	Yes
<b>Performance ratings</b>		
Performance areas	EN 1307	23 Domestic - Heavy
	eTL	10 Years
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Suitable for underfloorheating	ISO 8302	Yes
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
<b>Safety &amp; Environment</b>		
CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.005
<b>Guides</b>		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
<b>Manufacturer</b>		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC

---

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified

---