

Cantana Square

Product description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitée antisalissure



ege

design · quality · respect

| Product description | Methods | Product data |
|---------------------------------|----------------------------|-----------------------------|
| Construction | | |
| Structure | ISO 2424 | Tufted loop pile |
| Gauge | ISO 2424 | 1/16 |
| Pile material | DIR 96/73, 96/74 | 100% Polypropylen |
| Coloration | - | Solution dyed |
| Backing | eTL | HL - High foam |
| Dimensions | CEN/TS 14159 | Ca. 400 cm |
| Total thickness | ISO 1765 | Ca. 9,5 mm. |
| Surface pile thickness | ISO 1766 | Ca. 3,5 mm. |
| Tufts | ISO 1763 | Ca. 145.000 pr.m2 |
| Total carpet weight | ISO 8543 | Ca. 2.700 g/m2 |
| Pile yarn weight | eTL | 800 g/m2 |
| Surface pile density | ISO 8543 | Ca. 0,115 g/cm3 |
| ege soil protection | eTL | Yes |
| Performance ratings | | |
| Performance areas | EN 1307 | 23 Domestic - Heavy |
| | eTL | 10 Years |
| Suitable for use on stairs | EN 1963 | Domestic use only |
| Static control | eTL | Permanently antistatic |
| Body walking test | EN 1815 | Antistatic |
| Suitable for underfloorheating | ISO 8302 | Yes |
| Colour fastness to Light | ISO 105-B02 | 7 |
| Colour fastness to rubbing wet | EN ISO 105-X12 | 5 |
| Colour fastness to Rubbing Dry | EN ISO 105-X12 | 5 |
| Colourfast. to Water Patterned | EN ISO 105-E01 | 5 |
| Safety & Environment | | |
| CE Labeling | EN 14041 | Certified |
| | Declaration of Performance | DOP 9711-E |
| Indoor air | DIM Certifikat | No.005 |
| Guides | | |
| Installation+adhensive guide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| Spec. advice for this product | eTL | Dan/Eng/Deu/Fra |
| Cleaning, stain removal | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| Manufacturer | | |
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |

| Product description | Methods | Product data |
|----------------------------|----------------|-------------------------------|
| | EMAS | Audited and verified by BVC |
| | OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |
| | TransQ | Qualified |
