

Highline 910 on IP - Impervious

Product description



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Millitron
Backing	eTL	IP - Impervious
Dimensions	CEN/TS 14159	Ca. 400 cm
Total thickness	ISO 1765	Ca. 7,5 mm.
Surface pile thickness	ISO 1766	Ca. 5,0 mm.
Tufts	ISO 1763	Ca. 236.000 pr.m2
Total carpet weight	ISO 8543	Ca. 2.400 g/m2
Pile yarn weight	eTL	910 g/m2
	.	26.85 oz./yd2
Surface pile density	ISO 8543	Ca. 0,145 g/cm3
ege soil protection	eTL	Yes
MRSA protection	eTL	Yes
Performance ratings		
Performance areas	EN 1307	33 Commercial - Heavy
Castor chair suitability	EN 985	Yes, constant use
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Suitable for underfloorheating	ISO 8302	Yes
Light reflectance	eTL	Testreport
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
Safety & Environment		
CE Labeling	EN 14041	Certified
	Declaration of Performance	DOP 9711-E
Indoor air	DIM Certifikat	No.006
	GECA	Approved
Guides		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Manufacturer		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC

Product description	Methods	Product data
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified
