


Carré Ecotrust on Ecotrust 350, 100% Recycled

Product description



ege[®]
design · quality · respect

Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% Recycled Econyl Polyamide
Coloration	-	Millitron
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96 cm
Total thickness	.	0.28"
	ISO 1765	Ca. 7,0 mm.
Surface pile thickness	ISO 1766	Ca. 3,0 mm.
Tufts	ISO 1763	Ca. 183.000 pr.m2
Total carpet weight	.	64.9 oz./yd2
	ISO 8543	Ca. 2.200 g/m2
Pile yarn weight	eTL	440 g/m2
	.	12.98 oz./yd2
Surface pile density	ISO 8543	Ca. 0,100 g/cm3
ege soil protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Klasse 33
Castor chair suitability	EN 985	Yes, constant use
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	25 dB
Acoustical absorption	eTL	0,25 aW
Suitable for underfloorheating	ISO 8302	Yes
Colour fastness to Light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	EN ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to Water Patterned	EN ISO 105-E01	>4
Cleaning	AATCC 138	4.0
Colour fastness to Ozone	AATCC 129	4.5
Colour fast.Oxides of Nitrogen	AATCC 164	4.5
Other performance tests	ASTM D5252 Hexapod	4.0/3.5
	-	Commercial - Heavy
	AATCC 134 Electrostatic propensity	1.9 kV

Safety & Environment

CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10017C ECT
CE Labeling	Declaration of Performance	DOP 9711-17CECT
Fire classification	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-441
	CH,VKF/AEAI	Cfl-s1
	ASTM E-648	Class 1

Product description	Methods	Product data
Indoor air	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN13501-1 euro class	Cfl-s1
	DIM Certifikat	No.006
	BASTA	Registered
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
Environment	Environmental Choice NZ	Approved
	GECA	Approved
	BRE	ENP 434
	Byggvarudeklaration	BVD 3
	BREEAM-NOR	With EcotrustA Backing
	Recycled Content, ISO 14021	Ca. 41 %
	Recycled Content for LEED	Ca. 36 %

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified