

Highline 1100 Ecotrust on Ecotrust 1500, 100% Recycled

Product description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traitee antisalissure



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% Recycled Econyl Polyamide
Coloration	-	Millitron
Backing	eTL	Ecotrust 1500, 100% Recycled
Dimensions	ISO 3018	48x48/96x96 cm
Dimensional stability	eTL	<0,2%
Total thickness	eTL	Ca. 13,0 mm.
Surface pile thickness	eTL	Ca. 5,5 mm.
Total carpet weight	eTL	Ca. 4.200 g/m ²
Pile yarn weight	eTL	1.100 g/m ²
Surface pile density	eTL	Ca. 0,160 g/cm ³
edge soil protection	eTL	Yes

Performance ratings

Performance areas	eTL	33 Commercial - Heavy
Castor chair suitability	eTL	Yes, constant use
Static control	eTL	Permanently antistatic
Acou.insu. from impact noise	EN ISO 717-2	28 dB
Acoustical absorption	ISO 354	0,30 aW
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4

Safety & Environment

CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10018C ECT
CE Labeling	Declaration of Performance	DoP 9711-18CECT
Indoor air	DIM Certifikat	No.006
Environment	Recycled Content, ISO 14021	Ca. 64 %
	Recycled Content for LEED	Ca. 58 %

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC

Product description	Methods	Product data
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified