

# Highline 630 Ecotrust on Ecotrust 1500, 100% Recycled

## Product description

---



Antismudsbehandlet  
Antisoiling protected  
Schmutzabweisend  
Traînée antisalissure



Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Millitron
Backing	eTL	Ecotrust 1500, 100% Recycled
Dimensions	ISO 3018	48x48/96x96 cm
Total thickness	eTL	Ca. 11,5 mm.
Surface pile thickness	eTL	Ca. 4,0 mm.
Total carpet weight	eTL	Ca. 4.100 g/m2
Pile yarn weight	eTL	630 g/m2
Surface pile density	eTL	Ca. 0,110 g/cm3
edge soil protection	eTL	Yes
<b>Performance ratings</b>		
Static control	eTL	Permanently antistatic
Acou.insu. from impact noise	eTL	27 dB
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
<b>Safety &amp; Environment</b>		
CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10018C ECT
CE Labeling	Declaration of Performance	DoP 9711-18CECT
Indoor air	DIM Certifikat	No.006
Environment	Recycled Content, ISO 14021	Ca. 39 %
	Recycled Content for LEED	Ca. 39 %
<b>Guides</b>		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
<b>Manufacturer</b>		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified