

Highline 630 Ecotrust on Ecotrust 750, 100% Recycled

Product description



Antismudsbehandlet
Antisoiling protected
Schmutzabweisend
Traînée antisoissure



contract
CERTIFICATE



ege[®]

design · quality · respect

| Product description | Methods | Product data |
|------------------------|------------------|-----------------------------|
| Construction | | |
| Structure | ISO 2424 | Tufted cut pile |
| Gauge | ISO 2424 | 1/10 |
| Pile material | DIR 96/73, 96/74 | 100% Polyamide |
| Coloration | - | Millitron |
| Backing | eTL | Ecotrust 750, 100% recycled |
| Dimensions | CEN/TS 14159 | 48x48/96x96 cm |
| Dimensional stability | EN 986 | <0,2% |
| Total thickness | ISO 1765 | Ca. 10,0 mm. |
| Surface pile thickness | ISO 1766 | Ca. 4,5 mm. |
| Tufts | ISO 1763 | Ca. 240.000 pr.m2 |
| Total carpet weight | ISO 8543 | Ca. 2.800 g/m2 |
| Pile yarn weight | eTL | 630 g/m2 |
| Surface pile density | ISO 8543 | Ca. 0,100 g/cm3 |
| edge soil protection | eTL | Yes |

Performance ratings

| | | |
|--------------------------------|----------------|------------------------|
| Performance areas | EN 1307 | 33 Commercial - Heavy |
| Wear guarantee | eTL | Contract certificate |
| Performance areas | Gulvbranchen | Klasse 33 |
| Castor chair suitability | EN 985 | Yes, constant use |
| Suitable for use on stairs | EN 1963 | Yes |
| Static control | eTL | Permanently antistatic |
| Body walking test | EN 1815 | Antistatic |
| Vertical resistance | ISO/DIS 10965 | <1x10.10 ohm |
| Acou.insu. from impact noise | EN ISO 717-2 | 28 dB |
| Acoustical absorption | ISO 354 | 0,30 aW |
| Suitable for underfloorheating | ISO 8302 | Yes |
| Colour fastness to Light | ISO 105-B02 | >5 |
| Colour fastness to rubbing wet | EN ISO 105-X12 | >3 |
| Colour fastness to Rubbing Dry | EN ISO 105-X12 | >3-4 |
| Colourfast. to Water Patterned | EN ISO 105-E01 | >4 |

Safety & Environment

| | | |
|---------------------|--------------------------------|------------------------|
| CE Labeling | EN 14041 | Certified |
| EC Certificate | EN 14041 | 2531-CPR-CXA10018C ECT |
| CE Labeling | Declaration of Performance | DoP 9711-18CECT |
| Fire classification | DK,MK GODKENDELSE | Godkendt |
| | D,DIBT AbZ.no. | Z-156.601-441 |
| | CH,VKF/AEAI | Cfl-s1 |
| Indoor air | DIM Certifikat | No.006 |
| | BASTA | Registered |
| | GreenLabel Singapore | Approved |
| | Emissions dans l'air intérieur | A+/A+ |
| | Environmental Choice NZ | Approved |
| | GECA | Approved |
| Environment | Byggvarudeklaration | BVD 3 |
| | Recycled Content, ISO 14021 | Ca. 31 % |
| | Recycled Content for LEED | Ca. 31 % |

Guides

| | | |
|------------------------------|----|-------|
| Installation+adhensive guide | DK | Dansk |
|------------------------------|----|-------|

| Product description | Methods | Product data |
|----------------------------|----------------|---------------------|
| Cleaning, stain removal | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer

| | | |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |
| | TransQ | Qualified |