

# Highline Loop Ecotrust on Ecotrust 1500, 100% Recycled

## Product description

---



Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Millitron
Backing	eTL	Ecotrust 1500, 100% Recycled
Dimensions	ISO 3018	48x48/96x96 cm
Total thickness	eTL	Ca. 11,5 mm.
Surface pile thickness	eTL	Ca. 4,0 mm.
Total carpet weight	eTL	Ca. 4.100 g/m2
Pile yarn weight	eTL	680 g/m2
Surface pile density	eTL	Ca. 0,130 g/cm3
edge soil protection	eTL	Yes
<b>Performance ratings</b>		
Performance areas	eTL	33 Commercial - Heavy
Castor chair suitability	EN 985	Yes, constant use
Static control	eTL	Permanently antistatic
Acou.insu. from impact noise	EN ISO 717-2	27 dB
Acoustical absorption	ISO 354	0,30 aW
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
<b>Safety &amp; Environment</b>		
CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10017C ECT
CE Labeling	Declaration of Performance	DOP 9711-17CECT
Fire classification	DK,MK GODKENDELSE	Godkendt
Indoor air	DIM Certifikat	No.006
Environment	Recycled Content, ISO 14021	Ca. 39 %
	Recycled Content for LEED	Ca. 39 %
<b>Guides</b>		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
<b>Manufacturer</b>		
Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified