

# Highline Loop Ecotrust on Ecotrust 750, 100% Recycled

Product description



Antismudsbehandlet  
Antisoiling protected  
Schmutzabweisend  
Traînée antisoissure



contract  
CERTIFICATE



**ege**<sup>®</sup>

design · quality · respect

Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Millitron
Backing	eTL	Ecotrust 750, 100% recycled
Dimensions	CEN/TS 14159	48x48/96x96 cm
Dimensional stability	EN 986	<0,2%
Total thickness	ISO 1765	Ca. 10,0 mm.
Surface pile thickness	ISO 1766	Ca. 4,5 mm.
Tufts	ISO 1763	Ca. 167.000 pr.m2
Total carpet weight	ISO 8543	Ca. 3.300 g/m2
Pile yarn weight	eTL	680 g/m2
Surface pile density	ISO 8543	Ca. 0,100 g/cm3
edge soil protection	eTL	Yes

### Performance ratings

Performance areas	EN 1307	33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Klasse 33
Castor chair suitability	EN 985	Yes, constant use
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Vertical resistance	ISO/DIS 10965	<1x10.9 ohm
Acou.insu. from impact noise	EN ISO 717-2	29 dB
Acoustical absorption	ISO 354	0,30 aW
Suitable for underfloorheating	ISO 8302	Yes
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>3-4
Other performance tests	ASTM D2646 Breaking Strength	542/682 lbf
	AATCC 175 Stain resistance	4
	AATCC 134 Electrostatic propensity	1,8 kV
	AATCC 165 Crocking Wet/ Dry	5/5

### Safety & Environment

CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10017C ECT
CE Labeling	Declaration of Performance	DOP 9711-17CECT
Fire classification	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-440
	CH,VKF/AEAI	Cfl-s1
	GB,BS 4790	Low
Indoor air	DIM Certifikat	No.006
	AATCC 174 Mildew/Rot resist.	2/NZ
	BASTA	Registered
	GreenLabel Singapore	Approved
	Emissions dans l'air intérieur	A+/A+
	Environmental Choice NZ	Approved

Product description	Methods	Product data
Environment	GECA	Approved
	Byggvarudeklaration	BVD 3
	Recycled Content, ISO 14021	Ca. 26 %
	Recycled Content for LEED	Ca. 26 %

### Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

### Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified