

# Highline 80/20 1400 Ecotrust on Ecotrust 1500, 100% Recycled

## Product description

---



Antismudsbehandlet  
Antisoiling protected  
Schmutzabweisend  
Traîée antisalissure



Impregneret mod klædemøl  
Anti clothes moth treated  
Gegen Kleidermotten impr.  
Traîée anti-mites de draps



Product description	Methods	Product data
<b>Construction</b>		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	80% Pure new wool 20% Polyamid
Coloration	-	Millitron
Backing	eTL	Ecotrust 1500, 100% Recycled
Dimensions	ISO 3018	48x48/96x96 cm
Dimensional stability	eTL	<0,2%
Total thickness	eTL	Ca. 14,5 mm.
Surface pile thickness	eTL	Ca. 6,5 mm.
Total carpet weight	eTL	Ca. 4.300 g/m <sup>2</sup>
Pile yarn weight	eTL	1.400 g/m <sup>2</sup>
Surface pile density	eTL	Ca. 0,160 g/cm <sup>3</sup>
edge soil protection	eTL	Yes
Anti-1-spotted clothes moths	eTL	Yes
<b>Performance ratings</b>		
Performance areas	eTL	33 Commercial - Heavy
Castor chair suitability	eTL	Yes, constant use
Suitable for use on stairs	eTL	No
Static control	eTL	Permanently antistatic
Acou.insu. from impact noise	eTL	31 dB
Acoustical absorption	eTL	0,40 aW
Suitable for underfloorheating	ISO 8302	No
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
<b>Safety &amp; Environment</b>		
CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10020BECT
CE Labeling	Declaration of Performance	DOP 9711-20BECT
Indoor air	DIM Certifikat	No.006
Environment	Recycled Content, ISO 14021	Ca. 37 %
	Recycled Content for LEED	Ca. 37 %
<b>Guides</b>		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
<b>Manufacturer</b>		
Factory certification	ISO 9001	Audited and verified by BVC

<b>Product description</b>	<b>Methods</b>	<b>Product data</b>
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified