

Highline 80/20 1400 Ecotrust on Ecotrust 350, 100% Recycled

Product description



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	80% Pure new wool 20% Polyamid
Coloration	-	Millitron
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96 cm
Dimensional stability	EN 986	<0,2%
Total thickness	ISO 1765	Ca. 10,5 mm.
Surface pile thickness	ISO 1766	Ca. 6,0 mm.
Tufts	ISO 1763	Ca. 139.000 pr.m2
Total carpet weight	ISO 8543	Ca. 3.000 g/m2
Pile yarn weight	eTL	1.400 g/m2
Surface pile density	ISO 8543	Ca. 0,160 g/cm3
edge soil protection	eTL	Yes
Anti-1-spotted clothes moths	eTL	Yes
Performance ratings		
Performance areas	EN 1307	33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Klasse 33
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	28 dB
Acoustical absorption	eTL	0,35 aW
Suitable for underfloorheating	ISO 8302	Yes
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
Safety & Environment		
CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10020BECT
CE Labeling	Declaration of Performance	DOP 9711-20BECT
Fire classification	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-479
	CH,VKF/AEAI	Bfl-s1
	IMO	Certified
	USCG	USCG 164.117/EC0575/6897
	EC Type-Ex.Cert.No.	MED-B-6668
	QS-Cert.of.Assesment-EC No.	MED-D-1257
Indoor air	DIM Certifikat	No.006
	BASTA	Registered
	Emissions dans l'air intérieur	A+/A+
Environment	Recycled Content, ISO 14021	Ca. 15 %
	Recycled Content for LEED	Ca. 15 %
Guides		
Installation+adhensive guide	DK	Dansk
	N	Norsk

Product description	Methods	Product data
Cleaning, stain removal	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
F	Francais	

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified