

CREATE! any shape

Product description



Product description	Methods	Product data
Construction		
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	1/8
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Millitron
Backing	eTL	WT - Woven textile
Dimensions	CEN/TS 14159	Ca. 400 cm
Total thickness	ISO 1765	Ca. 8,0 mm.
Surface pile thickness	ISO 1766	Ca. 5,5 mm.
Tufts	ISO 1763	Ca. 199.000 pr.m2
Total carpet weight	ISO 8543	Ca. 2.600 g/m2
Pile yarn weight	eTL	1.100 g/m2
Surface pile density	ISO 8543	Ca. 0,155 g/cm3
edge soil protection	eTL	Yes
Performance ratings		
Performance areas	EN 1307	33 Commercial - Heavy
Wear guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Klasse 33
	UPEC	U3 P3 E1 C0
	UPEC approval No.	12/290
Castor chair suitability	EN 985	Yes, constant use
Suitable for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	EN ISO 717-2	27 dB
Acoustical absorption	ISO 354	0,20 aW
Suitable for underfloorheating	ISO 8302	Yes
Light reflectance	eTL	Testreport
Colour fastness to Light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to Rubbing Dry	EN ISO 105-X12	>3-4
Colourfast. to Water Patterned	EN ISO 105-E01	>4
Other performance tests	Golf Spike Resistance Test	3,2
Safety & Environment		
CE Labeling	EN 14041	Certified
EC Certificate	EN 14041	2531-CPR-CXA10004C
CE Labeling	Declaration of Performance	DOP 9711-4C
Fire classification	DK,MK GODKENDELSE	Godkendt
	D,DIBT AbZ.no.	Z-156.601-441
	CH,VKF/AEAI	Cfl-s1
Indoor air	DIM Certifikat	No.006
	INSTA 800	Dust level 5
	BASTA	Registered
	Emissions dans l'air intérieur	A+/A+
Environment	Byggvarudeklaration	BVD 3
	Environmental Product Decl.	EPD GUT 2009211-E

Product description	Methods	Product data
Guides		
Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified