



SAFETY DATA SHEET

STYCCOBOND F81 RESIN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STYCCOBOND F81 RESIN
Product number F3676
Internal identification SBF81R/10

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Component of Epoxy Resin adhesive.
Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier F.Ball and Co. Ltd.
 Churnetside Business Park,
 Station Road,
 Cheddleton,
 Leek,
 Staffordshire. ST13 7RS
 Tel: 01538 361633 Mon-Fri 8.30am-5.00pm (Exc Bank Holidays)
 Fax: 01538 361622
 E.mail: msds@f-ball.co.uk

1.4. Emergency telephone number

Emergency telephone 01538 361633 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Not Classified

Health hazards

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards

Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

Xi;R36/38. R43. N;R51/53.

Human health

The liquid is irritating to eyes and skin. Risk of sensitisation by skin contact

Environmental

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Pictogram

STYCCOBOND F81 RESIN**Signal word****Hazard statements****Warning**

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P313 Get medical advice/attention.

Contains

EPOXY RESIN (Number average MW <= 700), OXIRANE, MONO [(C12-14-ALKYLOXY)METHYL] DERIVS, BISPHENOL TYPE F EPOXY RESIN

Supplementary precautionary statements

P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

EPOXY RESIN (Number average MW <= 700)	30-60%
CAS number: 25068-38-6 EC number: 500-033-5 REACH registration number: 01-2119456619-26	
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
BISPHENOL TYPE F EPOXY RESIN	5-10%
CAS number: 54208-63-8 EC number: 500-033-5	
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	Xi;R36/38. N;R51/53. R43.
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS	5-10%
CAS number: 68609-97-2 EC number: — REACH registration number: 01-2119485289	
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	R43 Xi;R38
Skin Sens. 1 - H317	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

STYCCOBOND F81 RESIN

Composition comments Epoxy resin blend.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from source of contamination.

Inhalation

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention immediately.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

This is unlikely to occur but symptoms similar to those of ingestion may develop.

Ingestion

May cause discomfort if swallowed.

Skin contact

Skin irritation. May cause an allergic skin reaction.

Eye contact

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Toxic gases/vapours/fumes of: Oxides of the following substances: Carbon. Nitrogen.

Hazardous combustion products

Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting

No specific firefighting precautions known.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

STYCCOBOND F81 RESIN

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid discharge into drains or watercourses or onto the ground. Contain spillages with sand, earth or any suitable absorbent material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb spillage with sand or other inert absorbent. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Provide adequate ventilation. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep separate from food, feedstuffs, fertilisers and other sensitive material. Store in closed original container at temperatures between 5°C and 30°C. Store in a cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Personal protection

Always check applicability with your supplier of protective equipment.

Eye/face protection

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

STYCCOBOND F81 RESIN

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse.

Respiratory protection

In case of inadequate ventilation use a respirator suitable for organic vapours. Consult respirator manufacturer for specific advice.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Paste.

Colour

Yellow.

Odour

Slight. Aromatic.

pH

pH (concentrated solution): N/A

Flash point

N/A°C

Relative density

1.31 approx @ @ 20 degC°C

Viscosity

2160 approx P @ 20 degC°C

9.2. Other information

Other information

None.

Volatility

N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

The following materials may react with the product: Acids. Strong alkalis. Strong oxidising agents.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Conditions to avoid

Considerable exothermic reaction can occur when mixed with epoxide hardeners.

10.5. Incompatible materials

Materials to avoid

Strong acids. Strong alkalis. Strong oxidising agents.

10.6. Hazardous decomposition products

STYCCOBOND F81 RESIN

Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects

No information available.

General information

No specific health hazards known.

Inhalation

May cause some discomfort in poorly ventilated areas.

Ingestion

May cause discomfort if swallowed.

Skin contact

Prolonged or repeated exposure may cause severe irritation. May cause sensitisation by skin contact.

Eye contact

Irritating to eyes.

Acute and chronic health hazards

Irritating to skin. Irritating to eyes. May cause sensitisation by skin contact.

Route of entry

Skin and/or eye contact

Target organs

Eyes Skin

Medical symptoms

Skin irritation. Irritation of eyes and mucous membranes.

Medical considerations

Pre-existing eye problems. Skin disorders and allergies.

STYCCOBOND F81 RESIN**Toxicological information on ingredients.****EPOXY RESIN (Number average MW <= 700)****Acute toxicity - oral****Acute toxicity oral (LD₅₀ mg/kg)**

2,000

Species

Rat

Acute toxicity - dermal**Acute toxicity dermal (LD₅₀ mg/kg)**

2000

Species

Rat

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS**Acute toxicity - oral****Acute toxicity oral (LD₅₀ mg/kg)**

17,100

Species

Rat

POLYETHER MODIFIED TRISILOXANE**Acute toxicity - dermal****ATE dermal (mg/kg)**

1100

Acute toxicity - inhalation**ATE inhalation (vapours mg/l)**

11.0

SECTION 12: Ecological Information

Ecotoxicity

The product should not be allowed to enter drains, sewers or watercourses. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Not available

STYCCOBOND F81 RESIN

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - fish

LC50, 96 hours: 1.3 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates

EC50, 48 hours: 2.1 mg/l, Daphnia magna

Acute toxicity - aquatic plants

, 72 hours: > 11 mg/l, Freshwater algae

Acute toxicity - microorganisms

EC50, 3 hours: > 100 mg/l, Activated sludge

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

Acute toxicity - fish

LC50, 96 hours: > 1800 , Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates

EC50, 48 hours: 844 mg/l, Daphnia magna

Acute toxicity - microorganisms

EC50, >: > 100 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility

The product is non-volatile.

12.5. Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Small quantities of product may be treated with an equivalent quantity of product hardener, allowed to cure and disposed of as low hazard waste.

Large quantities should be disposed of via licensed waste operators to an approved incineration unit. Product containers must not be re-used without commercial cleaning.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), POLYETHER MODIFIED TRISILOXANE)
--------------------------------	---

STYCCOBOND F81 RESIN

Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), POLYETHER MODIFIED TRISILOXANE)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), POLYETHER MODIFIED TRISILOXANE)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), POLYETHER MODIFIED TRISILOXANE)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID subsidiary risk	
ADR/RID label	9
IMDG class	9
IMDG subsidiary risk	
ICAO class/division	9
ICAO subsidiary risk	
Transport labels	

**14.4. Packing group**

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



Yes.

14.6. Special precautions for user

EmS	F-A, S-F
Emergency Action Code	3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Control of Substances Hazardous to Health Regulations 2002 (as amended).

Guidance

Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006)

STYCCOBOND F81 RESIN

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information

F.Ball and Company Ltd Technical Datasheet.

Key literature references and sources for data

Type of Regulated Adhesive under the air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong (VCT and Asphalt Tile Adhesive). VOC Content (after mixing with hardener) not exceeding 1g/litre.

Revision comments

Section 16 change

Revision date 10/03/2015

Revision 10

Supersedes date 30/09/2014

SDS status Approved.

Risk phrases in full

R20 Harmful by inhalation.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard statements in full

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.