

PRIOR™ 16
Modular tiles for entrance flooring solutions

Product description	UV resistant PVC modular tile		
	Wear resistance	Heavy	
	Total thickness	16mm	
	Total Weight	8180g/m ² (+/- 5%)	
Tile Construction	Composition	100% PVC	
	Mass	8180g/m ²	
	Backing thickness	16mm	
Performance Testing	Flammability	Low radius of effect	(BS 4790 Hot Nut Test)
	Wear Resistance	Pass at 66,000 cycles	(Vettermann Drum)
	Slip Resistance	DS (0.64)	(EN 13893)
	Antistatic Behaviour	Approx. 10 ¹³ ohms	(ISO 10965)
	Personal Charging	4.3kV	(ISO 6356)
	Static Load Resistance	To be confirmed	(BS 4939)
Tile Size	Nominal 200 x 200mm		
	Usable 195 x 195mm when installed		
Carbon Negative (Milliken Manufacturing Facility)		Yes	
ADA / BS 8300 / ISO 21542 Compliant		Yes	
LEED® Point Contributor		Yes	
ISO Manufacturing Certification		ISO 9001	
ISO Environmental Certification		ISO 14001	
Origin		CH	
Warranty		Please refer to our written warranty	

Please Note: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/ labelling /processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labelling, marketing, etc. All sales are exclusively subject to our standard terms of sales posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.