


## Conos

## 6323-K30D15

Conos



### Track Mounted Adjustable Spotlight with LED

- Light head: 350° rotation and up to 90° lockable tilting.
- Control gear housing and light head made of die cast aluminium.
- Optical grade metalized polycarbonate reflector.
- 3 circuit universal track adaptor.
- Passive cooling COB LED source 3000K CRI>80 of 4660 nominal lumen.
- System power 47W; System efficacy 77,3 lm/W; 3635 delivered lumen.
- Optic: reflector beam angle: 15°.
- 220-240V 50/60Hz integral control gear is inclusive.
- Versions for G12 CDM-T or E27 PAR30 CDM-R or GX8,5 CDM-R111 MH or G53 AR111 Halogen or PAR30 E27 LED retrofit lamps are available.

LED source package is available on request with a preferred LED colour rendering CRI>90 and/or other colour temperature K options.

### Accessories

(To be ordered separately)

Item	Code
Ceiling Base	2049

### Specifications

Designed and manufactured to comply with European standard EN 60598.



Product code	Finish	Color temperature	CRI	Beam angle	Dim. options	Code
6323	10 - Black	<b>K30-3000K</b>	>80	<b>D15-15°</b>	Phase	2
	11 - White				LaserDIM	5
	75 - Grey					

Ordering code example : 6323 - \_\_ K30 D15 \_\_