


Mini Mondo

6320-K30D40

Mondo



Track Mounted Adjustable Spotlight with LED

- Light head: 350° rotation and up to 85° aiming angle.
- Made from die cast aluminium, light head designed with integrated heat-sink.
- Optical grade metalized polycarbonate reflector.
- 3 circuit universal track adaptor.
- Passive cooling COB LED source 3000K CRI>80 of 2540 nominal lumen.
- System power 27W; System efficacy 74,1 lm/W; 2000 delivered lumen.
- Optic: reflector beam angle: 40°.
- 220-240V 50/60Hz integral control gear is inclusive.
- Accepts up to 3 flat optical accessories.
- Versions for PAR20 CDM-R or G8,5 CDM-TC or GX10 MR16 MH or GU5,3 MR16 Halogen or retrofit or PAR20 E27 LED retrofit lamps are available.

LED source package is available on request with a preferred LED colour rendering CRI>90 and/or other colour temperature K options.

Accessories

(To be ordered separately)

Item	Code
Coloured Filters	2695
Honeycomb Louvre	2693
Anti-Glare Tube	2694
Directional Flaps	2692
Wallwasher Visor	2386

Specifications

Designed and manufactured to comply with European standard EN 60598.



Product code	Finish	Color temperature	CRI	Beam angle	Dim. options	Code
6320	10 - Black	K30-3000K	>80	D40-40°	Phase	2
	11 - White				LaserDIM	5
	29 - Grey					

Ordering code example : 6320 - __ K30 D40 __