

**Number: UK9-54**

**DECLARATION OF PERFORMANCE**

In accordance with Annex III of Registration (EU) No. 305/2011

**(Construction Product Regulation)**

**For the product Proofex 3000**

1. Unique identification code of the product-type:  
**EN 13707 Flexible sheet for waterproofing**
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):  
**Batch Number: See product packaging**
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:  
**EN13707: Flexible sheet for waterproofing**  
**EN13969: Flexible sheet for waterproofing**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



**Fosroc Limited**  
**Drayton Manor Business Park**  
**Coleshill Road, Tamworth**  
**Staffordshire, B78 3 TL, UK**

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

**Not Relevant**

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

**System 2+**

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

The notified body, SGS Ltd, identification number 0120, has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 2+ and issued the following:

**Certificate of Factory Production Control**

**No. 0120-CPD-GB08/75673**

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

**Not Relevant**

9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
<b>Thickness</b>	1.5 mm	EN 1849-1
<b>Tensile Properties</b>	Long. 215 N/50mm Trans. 220 N/50mm	EN 12311-1
<b>Elongation at break</b>	Long. 324%	EN 12311-1

## Number: UK9-54

	Trans. 238%	
<b>Resistance to impact</b>	Met. A 500 mm Met. B 1000 mm	EN 12691
<b>Resistance to static load</b>	Met. A 10 kg Met.B 15 kg	EN 12730
<b>Resistance to tearing</b>	Long. 125 N Trans. 65 N	EN 12310-1
<b>Watertightness</b>	>= 60 kPa	EN 1928
<b>Water vapour properties</b>	3.4339E-9 kg/m <sup>2</sup> S vapour impermeable	EN 1931

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

### Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:



Jeremy Bell,  
Technical Quality Manager

Place and Date of Issue:      28/06/2013      Tamworth