

Number: UK9-55


DECLARATION OF PERFORMANCE

In accordance with Annex III of Registration (EU) No. 305/2011

(Construction Product Regulation)

For the product Proofex 3000MR

1. Unique identification code of the product-type:
EN 13707 Flexible sheet for waterproofing
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):
Batch Number: See product packaging
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:
EN13707: Flexible sheet for waterproofing
EN13969: Flexible sheet for waterproofing
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



Fosroc Limited
 Drayton Manor Business Park
 Coleshill Road, Tamworth
 Staffordshire, B78 3 TL, UK

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

Not Relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

System 2+

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

The notified body, SGS Ltd, identification number 0120, has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 2+ and issued the following:

Certificate of Factory Production Control
No. 0120-CPD-GB08/75673

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

Not Relevant

9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Thickness	1.2 mm	EN 1849-1
Tensile Properties	long. 150 N/50mm Trans. 150 N/50mm	EN 12311-1
Elongation at break	Long. >20%	EN 12311-1

Number: UK9-55


	Trans. >20%	
Resistance to impact	NPD	EN 12691
Resistance to static load	Met. A 15 kg Met. B 20 kg	EN 12730
Resistance to tearing	Long. 70 N Trans. 70 N	EN 12310-1
Watertightness	≥ 60 kPa	EN 1928
Water vapour properties	Sd ≥ 1500 m Vapour impermeable	EN 1931

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:



Jeremy Bell,
Technical Quality Manager

Place and Date of Issue: 28/06/2013 Tamworth