

Number: UK9-60

DECLARATION OF PERFORMANCE

In accordance with Annex III of Registration (EU) No. 305/2011

(Construction Product Regulation)

For the product **Proofex Cavitydrain 200**

1. Unique identification code of the product-type:
Proofex Cavitydrain 200
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):
Batch Number: See product packaging
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:
EN 13252: Geotextiles and related products, for use in drainage systems
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



Fosroc Limited
Drayton Manor Business Park
Coleshill Road, Tamworth
Staffordshire, B78 3XN, UK

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

Not Relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

System 2+

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

The notified body SKZ - TeConA GmbH, identification number 1213, has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 2+ and issued the following:

Certificate of Factory Production Control

No. 1213-CPD-5082

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

Not Relevant

9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Tensile strength, Tmax, MD	9 kN/m	EN ISO 10319
Tensile strength, Tmax, CMD	9 kN/m	EN ISO 10319
Elongation, εmax, MD	20%	EN ISO 10319
Elongation, εmax, CMD	20%	EN ISO 10319

Number: UK9-60


Compressive strength	150 kPa	EN ISO 25619-2
Cone drop penetration, DC (GTX)	NPD	EN ISO 13433
Static puncture resistance, Fp (GTX)	NPD	EN ISO 12236
Characteristic opening size, O90 (GTX)	NPD	EN ISO 12956
Water flow rate, qN (GTX)	NPD	EN ISO 11058
Water flow capacity, qp	10 l m ⁻¹ s ⁻¹	EN ISO 12958
Weathering resistance	Can be exposed up to 14 days.	EN 12224
Oxidation resistance	Durable in natural soil with 4<pH<9 and soil temperature <25°C for a minimum of 25 years' service life.	EN ISO 13438

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:



Jeremy Bell,
Technical Quality Manager

Place and Date of Issue: 22/04/2014 Tamworth