

Number: UK9-56

DECLARATION OF PERFORMANCE

In accordance with Annex III of Registration (EU) No. 305/2011

(Construction Product Regulation)

For the product Proofex Engage

1. Unique identification code of the product-type:
EN 13967 Flexible sheets for waterproofing
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):
Batch Number: See product packaging
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:
EN13967: Flexible sheet for waterproofing (Class Type A and Type T)
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



Fosroc Limited
Drayton Manor Business Park
Coleshill Road, Tamworth
Staffordshire, B78 3 TL, UK

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

Not Relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

System 2+

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

The notified body, BBA, identification number 0836, has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 2+ and issued the following:

Certificate of Factory Production Control

No. 0836-FPC-09/FO13

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

Not Relevant

9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Watertightness	No evidence of penetration at 6m head	EN 1928
Resistance to impact	1500 mm	EN 12691
Dangerous substances	Conforms with 5.17	
Resistance to static load	15 kg	EN 12730



Fosroc® Proofex Engage

Number: UK9-56

Elongation at break	Long. >300% Trans. >200%	EN 12311-1
Tensile Properties	Long. >10.0 N/mm ² Trans. >8.0 N/mm ²	EN 12311-1
Water vapour resistance after artificial ageing	Pass	EN 1296/EN 1931
Resistance to tearing	720 N (longitudinal)	EN 12310-1
Shear resistance of joints	>= 220 N (lap) >= 150 N (butt)	EN12317-1
Water vapour properties	Sd= 400 m	EN 1931
Length	30 m	EN1848-1
Width	1.27 m	EN1848-1
Thickness	4 -5 mm	EN 1849-1

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:

Jeremy Bell,
Technical Quality Manager

Place and Date of Issue: 28/06/2013 Tamworth