

Number: UK9-91

DECLARATION OF PERFORMANCE

In accordance with Annex III of Registration (EU) No. 305/2011

(Construction Product Regulation)

For the product Proofex LM

1. Unique identification code of the product-type:
Proofex LM
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):
Batch Number: See product packaging
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:
EN 15814: Polymer modified bituminous thick coatings (PMB) for waterproofing in below ground structures.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



Fosroc Limited
Drayton Manor Business Park
Coleshill Road, Tamworth
Staffordshire, B78 3TL, UK

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):
Not Relevant
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V
System 3
System 3 for reaction to fire
7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard
 The notified body Materialprüfungsamt Nordrhein-Westfalen, identification number 0432, performed the determination of the product-type on the basis of type testing under system 3 and the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued the following:
Report Numbers:
220005962-2 and 230006144-2
8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued
Not Relevant
9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Watertightness	W2A	EN 15814:2012
Crack bridging ability	CB2	
Water resistance	No discolouration of the water.	

Number: UK9-91


	No debonding from inlay.
Flexibility at low temperatures	No cracks
Dimensional stability at high temperatures	No sliding or draining down.
Reaction to fire	Class E
Resistance to compression	Class C2A
Durability of watertightness and reaction to fire	Passed

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:



Jeremy Bell,
Technical Quality Manager

Place and Date of Issue: 09/12/2013 Tamworth