



SAFETY DATA SHEET

PROOFEX WG BASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PROOFEX WG BASE
 Product number A2157001UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Base Component of Three Part Epoxy Flooring System

1.3. Details of the supplier of the safety data sheet

Supplier FOSROC Limited
 Drayton Manor Business Park
 Coleshill Road
 Tamworth
 Staffordshire
 B78 3XN
 Tel. +44 (0) 1827 262222
 Fax. +44 (0) 1827 262444
 enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Not Classified

Health hazards

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards

Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

Xi;R36/38. R43. N;R51/53.

Human health

The product is irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Pictogram



Signal word

Warning

Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

PROOFEX WG BASE

Precautionary statements

P261 Avoid breathing vapour/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with national regulations.

Contains

EPOXY RESIN (Type A) (Number average MW <= 700), EPOXY RESIN (Type F) (Number average MW <= 700), 2-ETHYL HEXYL GLYCIDYL ETHER

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Type A) (Number average MW <= 700) CAS number: 25068-38-6 EC number: 500-033-5	30-60%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC)
EPOXY RESIN (Type F) (Number average MW <= 700) CAS number: 9003-36-5 EC number: –	30-60%
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) R43 Xi;R36/38 N;R51/53
2-ETHYL HEXYL GLYCIDYL ETHER CAS number: 2461-15-6 EC number: 219-553-6	5-10%
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317	Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43,R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Get medical attention if any discomfort continues.

Inhalation

Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Give plenty of water to drink. Keep affected person under observation. Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

Eye contact

Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

PROOFEX WG BASE

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

May cause respiratory system irritation.

Ingestion

May cause discomfort if swallowed.

Skin contact

Skin irritation.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

No unusual fire or explosion hazards noted.

Hazardous combustion products

Carbon monoxide (CO). Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

No specific firefighting precautions known. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses. Provide adequate ventilation.

6.4. Reference to other sections

Reference to other sections

For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Provide adequate ventilation. Avoid the formation of mists. Avoid contact with skin and eyes.

PROOFEX WG BASE

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class

Chemical storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient comments

No exposure limits known for ingredient(s).

EPOXY RESIN (Type A) (Number average MW ≤ 700) (CAS: 25068-38-6)

DNEL	Workers - Inhalation; Short term systemic effects: 12.25 mg/m ³ Workers - Inhalation; Long term systemic effects: 12.25 mg/m ³
PNEC	- Fresh water; 0.006 mg/l

EPOXY RESIN (Type F) (Number average MW ≤ 700) (CAS: 9003-36-5)

DNEL	Workers - Inhalation; Long term systemic effects: 29.39 mg/m ³ Workers - Dermal; Long term systemic effects: 104.15 mg/kg/day
PNEC	- Fresh water; 0.003 mg/l - Marine water; 0.0003 mg/l

2-ETHYL HEXYL GLYCIDYL ETHER (CAS: 2461-15-6)

DNEL	Workers - Dermal; Long term : 4.17 mg/kg/day Workers - Dermal; Short term : 1 mg/kg/day
PNEC	- Fresh water; 0.002 mg/l - Marine water; 0.166 µg/l - Sediment (Freshwater); 0.177 mg/kg dw - Sediment (Marinewater); 0.018 mg/kg dw - STP; 0.017 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Nitrile rubber.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product. Do not smoke in work area.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs. It is recommended to use respiratory equipment with combination filter, type A2/P2.

PROOFEX WG BASE

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Colour

Straw.

Odour

Mild.

Odour threshold

Not determined.

pH

Not determined.

Melting point

Not determined.

Initial boiling point and range

> 200°C @ 1 atm

Flash point

> 200°C

Evaporation rate

Not determined.

Vapour pressure

0.001 kPa @ 20°C

Relative density

1.14 @ 20°C

Solubility(ies)

Insoluble in water.

Explosive properties

Not considered to be explosive.

Explosive under the influence of a flame

Not considered to be explosive.

Oxidising properties

Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information

Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Not relevant. Will not polymerise.

10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid

Amines. Acids Strong alkalis.

10.6. Hazardous decomposition products

When heated, vapours/gases hazardous to health may be formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

PROOFEX WG BASE**Inhalation**

Gas or vapour may irritate the respiratory system.

Ingestion

May cause discomfort if swallowed.

Skin contact

Irritating to skin. May cause sensitisation by skin contact.

Eye contact

Irritating to eyes.

Route of entry

Skin and/or eye contact

Toxicological information on ingredients.**EPOXY RESIN (Type A) (Number average MW <= 700)****Acute toxicity - oral**

Acute toxicity oral (LD50 mg/kg)

5,000.0

Species

Rat

Based on available data the classification criteria are not met.

ATE oral (mg/kg)

5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD50 mg/kg)

20000.0

Species

Rabbit

ATE dermal (mg/kg)

20000.0

Skin corrosion/irritation**Animal data**

(Rabbit)Moderate Irritation

Skin sensitisation

Sensitisation possible through skin contact.

2-ETHYL HEXYL GLYCIDYL ETHER**Acute toxicity - oral**

LD >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

LD >2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

LC (7 hr) 0.15 mg/l, Inhalation, Rat

SECTION 12: Ecological Information

Ecotoxicity

Dangerous for the environment. May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxic to aquatic organisms.

PROOFEX WG BASE**Ecological information on ingredients.****EPOXY RESIN (Type A) (Number average MW <= 700)****Acute toxicity - fish**

LC , 96 hours: 3.6 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates

EC , 48 hours: 2.8 mg/l, Daphnia magna

2-ETHYL HEXYL GLYCIDYL ETHER**Acute toxicity - fish**

LC , 96 hours: 5000 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates

EC , : 7.2 mg/l, Freshwater invertebrates

Acute toxicity - aquatic plants

NOEC, 72 hours: 500 mg/l, Freshwater algae

12.2. Persistence and degradability**Persistence and degradability**

The product is not expected to be biodegradable.

Ecological information on ingredients.**EPOXY RESIN (Type A) (Number average MW <= 700)****Persistence and degradability**

The product is not readily biodegradable.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

Ecological information on ingredients.**EPOXY RESIN (Type F) (Number average MW <= 700)****Partition coefficient**

: log Pow = Approximately 3.8 at 25 C

2-ETHYL HEXYL GLYCIDYL ETHER**Partition coefficient**

: 3.83

12.4. Mobility in soil**Mobility**

Not applicable.

Ecological information on ingredients.**EPOXY RESIN (Type A) (Number average MW <= 700)****Adsorption/desorption coefficient**

Soil - Koc: 445 @ °C

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.**EPOXY RESIN (Type A) (Number average MW <= 700)**

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****General information**

Waste is classified as hazardous waste.

Disposal methods

PROOFEX WG BASE

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



Yes.

14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant.

SECTION 15: Regulatory information

PROOFEX WG BASE

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance

Workplace Exposure Limits EH40. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 15/04/2015

Revision 5

SDS number 12283

Risk phrases in full

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard statements in full

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Disclaimer

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.



SAFETY DATA SHEET PROOFEX WG FILLER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PROOFEX WG FILLER

Product number A2157003UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Filler component of three part of epoxy resin system

1.3. Details of the supplier of the safety data sheet

Supplier FOSROC Limited
Drayton Manor Business Park
Coleshill Road
Tamworth
Staffordshire
B78 3XN
enquiryuk@fosroc.com
Tel. +44 (0) 1827 262222
Fax. +44 (0) 1827 262444

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Human health Dust may irritate the eyes and the respiratory system.

2.2. Label elements

Hazard statements NC Not Classified

Contains SILICA SAND

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PROOFEX WG FILLER

SILICA SAND	60 - 100%
CAS number: 14808-60-7	EC number: 238-878-4
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments Contains <1% respirable silica

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove affected person from source of contamination. Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.
Eye contact	Dust or splashes from the mixture may cause permanent eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products No known hazardous decomposition products.

5.3. Advice for firefighters

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of dust. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

PROOFEX WG FILLER

Methods for cleaning up Avoid generation and spreading of dust. Collect spillage with a shovel and broom, or similar and reuse, if possible.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of dust and contact with skin and eyes. Observe any occupational exposure limits for the product or ingredients.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³ Respirable crystalline silica

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of dust. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Dust-resistant, chemical splash goggles. (conform EN 166)

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

Wear a suitable dust mask. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Dust filter P2 (for fine dust). Dust filter P3 (for especially fine dust/powder) Particulate filters should comply with European Standard EN143.

PROOFEX WG FILLER

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	White/off-white.
Odour	Odourless.
pH	The product of hydrolysis (methanol) is readily biodegradable. Silicone content is not biodegradable. pH (diluted solution):
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Relative density	2.02 @ 25°C
Solubility(ies)	Insoluble in water.

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---------------------------------------------------------------------

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	----------------------------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
-------------------------------------------	----------------------

10.4. Conditions to avoid

Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
----------------------------	-----------------------------------------------------------------------------------

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	------------------------------------------------------------------------------------------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	No known hazardous decomposition products.
-----------------------------------------	--------------------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.
Eye contact	Dust in the eyes will cause irritation.

SECTION 12: Ecological Information

PROOFEX WG FILLER

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Not expected to be bioaccumulative

12.4. Mobility in soil

Mobility The product is not volatile but may be spread by dust-raising handling.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The material is inert and suitable for disposal at an approved solid waste disposal or landfill site.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

PROOFEX WG FILLER

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	10/09/2015
Revision	6
SDS number	12819

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

SAFETY DATA SHEET

PROOFEX WG HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name PROOFEX WG HARDENER
Product number A2157002UK9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener component of three part epoxy resin floor finish

1.3. Details of the supplier of the safety data sheet

Supplier FOSROC Limited
 Drayton Manor Business Park
 Coleshill Road
 Tamworth
 Staffordshire
 B78 3XN
 Tel. +44 (0) 1827 262222
 Fax. +44 (0) 1827 262444
 enquiryuk@fosroc.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Not Classified

Health hazards

Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards

Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC)

Xn;R22. C;R34. R43. R52/53.

Human health

Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Environmental

The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

PROOFEX WG HARDENER

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapour/spray.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with national regulations.
 P310 Immediately call a POISON CENTER/doctor.

Contains

TRIMETHYL HEXAMETHYLENEDIAMINE, PARA TOLUENE SULPHONIC ACID MONO HYDRATE

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

<p>TRIMETHYL HEXAMETHYLENEDIAMINE 60-100% CAS number: 25620-58-0 EC number: –</p>										
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Classification</td> <td style="width: 50%;">Classification (67/548/EEC or 1999/45/EC)</td> </tr> <tr> <td>Acute Tox. 4 - H302</td> <td>Xn;R22. C;R34. R43,R52/53.</td> </tr> <tr> <td>Skin Corr. 1B - H314</td> <td></td> </tr> <tr> <td>Skin Sens. 1 - H317</td> <td></td> </tr> <tr> <td>Aquatic Chronic 3 - H412</td> <td></td> </tr> </table>	Classification	Classification (67/548/EEC or 1999/45/EC)	Acute Tox. 4 - H302	Xn;R22. C;R34. R43,R52/53.	Skin Corr. 1B - H314		Skin Sens. 1 - H317		Aquatic Chronic 3 - H412	
Classification	Classification (67/548/EEC or 1999/45/EC)									
Acute Tox. 4 - H302	Xn;R22. C;R34. R43,R52/53.									
Skin Corr. 1B - H314										
Skin Sens. 1 - H317										
Aquatic Chronic 3 - H412										
<p>PARA TOLUENE SULPHONIC ACID MONO HYDRATE 1-5% CAS number: 6192-52-5 EC number: –</p>										
<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Classification</td> <td style="width: 50%;">Classification (67/548/EEC or 1999/45/EC)</td> </tr> <tr> <td>Met. Corr. 1 - H290</td> <td>Xi;R36/37/38.</td> </tr> <tr> <td>Skin Corr. 1B - H314</td> <td></td> </tr> <tr> <td>Eye Dam. 1 - H318</td> <td></td> </tr> <tr> <td>STOT SE 3 - H335</td> <td></td> </tr> </table>	Classification	Classification (67/548/EEC or 1999/45/EC)	Met. Corr. 1 - H290	Xi;R36/37/38.	Skin Corr. 1B - H314		Eye Dam. 1 - H318		STOT SE 3 - H335	
Classification	Classification (67/548/EEC or 1999/45/EC)									
Met. Corr. 1 - H290	Xi;R36/37/38.									
Skin Corr. 1B - H314										
Eye Dam. 1 - H318										
STOT SE 3 - H335										

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Ingestion

Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention immediately.

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information

PROOFEX WG HARDENER

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Ingestion

May cause chemical burns in mouth and throat.

Skin contact

May cause serious chemical burns to the skin. May cause sensitization by skin contact.

Eye contact

Eye contact may cause serious and potentially irreversible injuries.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting

No specific firefighting precautions known.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions

Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Do not touch or walk into spilled material. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Provide adequate ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class

PROOFEX WG HARDENER

Corrosive storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient comments

No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Polyvinyl chloride (PVC). Nitrile rubber. Viton rubber (fluoro rubber).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station and safety shower. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs. It is recommended to use respiratory equipment with combination filter, type A2/P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

Colour

Clear liquid.

Odour

Amine. Ammonia.

pH

pH (concentrated solution): 11 @ 1.1 mixture

Initial boiling point and range

> 230°C @ 1 atm

Flash point

110°C

Vapour pressure

0.002 kPa @ 20°C

Relative density

0.89 @ 20°C

Solubility(ies)

Immiscible with water.

PROOFEX WG HARDENER

Auto-ignition temperature

350°C

9.2. Other information

Other information

Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The following materials may react with the product: Acids. Alkalis. Oxidising materials.

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Not known. Will not polymerise.

10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid

Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)

511.24744376

Inhalation

Harmful by inhalation. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

Ingestion

Harmful if swallowed. May cause burns in mucous membranes, throat, oesophagus and stomach.

Skin contact

Causes burns. Harmful in contact with skin. May cause sensitisation by skin contact.

Eye contact

Causes burns. Risk of serious damage to eyes.

Acute and chronic health hazards

This product is corrosive.

Route of entry

Inhalation Ingestion. Skin and/or eye contact

Target organs

No specific target organs known.

Toxicological information on ingredients.

TRIMETHYL HEXAMETHYLENEDIAMINE

Acute toxicity - oral

Acute toxicity oral (LD50 mg/kg)

910

Species

Rat

Skin sensitisation

Sensitising.

PROOFEX WG HARDENER

SECTION 12: Ecological Information

Ecotoxicity

Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment

12.1. Toxicity

Ecotoxic to fish/daphnia/algae

Ecological information on ingredients.

TRIMETHYL HEXAMETHYLENEDIAMINE

Acute toxicity - fish

LC50, 48 hours: 174 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates

EC , 24 hours: 31.5 mg/l, Daphnia magna

Acute toxicity - aquatic plants

EC , 72 hours: 29.5 mg/l, Scenedesmus subspicatus

Acute toxicity - microorganisms

EC10, 16 hours: 72 mg/l, Pseudomonas putida

12.2. Persistence and degradability

Persistence and degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

12.4. Mobility in soil

Mobility

The product is insoluble in water.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Not relevant.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste material and any included combustible absorbent and containers should be suitable for incineration at an approved facility. Note that fully cured material is not considered as hazardous waste.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	2327
UN No. (IMDG)	2327
UN No. (ICAO)	2327
UN No. (ADN)	2327

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	TRIMETHYLHEXAMETHYLENEDIAMINES
Proper shipping name (IMDG)	TRIMETHYLHEXAMETHYLENEDIAMINES
Proper shipping name (ICAO)	TRIMETHYLHEXAMETHYLENEDIAMINES
Proper shipping name (ADN)	TRIMETHYLHEXAMETHYLENEDIAMINES

PROOFEX WG HARDENER**14.3. Transport hazard class(es)**

ADR/RID class	8
ADR/RID classification code	C7
ADR/RID label	8
IMDG class	8
ICAO class/division	8
ADN class	8

Transport labels**14.4. Packing group**

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

14.5. Environmental hazards**Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS	F-A, S-B
ADR transport category	3
Emergency Action Code	2X
Hazard Identification Number (ADR/RID)	80
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

Water hazard classification

Water hazard class 2 (German Regulation) (Self Assessment): hazardous for water.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information**General information**

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Revision comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date	15/04/2015
Revision	5

PROOFEX WG HARDENER

SDS number 12286

Risk phrases in full

R22 Harmful if swallowed.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard statements in full

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Disclaimer

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.