



## Profile 358 – 3D Secure Series

### Description

The 358 Secure Series has been specifically developed for the more challenging security environments, designed to give the highest level of security combined with unrivalled see through qualities making it an excellent choice for use with camera surveillance and yet this product does not have a negative impact on its surroundings in fact quite the reverse the product blends in to the background relatively unnoticed. Profile 358 offers the perfect security solution; the longest cut through delay time and almost unclimbable makes this product a formidable deterrent ... exactly the qualities specified the world over to create secure and safe environments.

### Benefits

- **Rigidity** – Heavy welded mesh panels combined with Horizontal “V” Beams guarantee a very high level of rigidity.
- **Security** – Mesh apertures of 12.7 x 76.2 combine to create a barrier which has the longest cut through time and makes the fence almost impossible to climb yet gives excellent visibility for camera surveillance.
- **Fully Compatible** – With detection and alarm systems.
- **Vandal Resistant** – Finger-proof apertures combined with 4mm diameter wires deters even the most determined intruders.

### Range

Fence Height	Panel Height / Width		“V” Beams	Fixings / Post	Post Centres
2.0m	2000mm	2515mm	2	6	2530mm
2.4m	2400mm	2515mm	3	7	2530mm
3.0m	3000mm	2515mm	3	10	2530mm

- **Complete System** – The system consists of a full range of panel heights complete with Posts and Security Fixings. In addition to the fencing we offer a full range of swing and sliding gates to complete the Security solution.
- **Appearance** – Excellent visibility making the fence a perfect partner to the use of cameras. Aesthetically pleasing and does not impose itself visually on its surroundings.
- **Life Time** – The life of a security fence will depend upon the quality of finish; Profile 358 3D Series offers the very best quality finish in the market. Starting with Pre galvanised material which is subjected to a rigorous cleaning process prior to the application of an architectural grade polyester resin powder coating.
- **Fast and Cost Effective Installation** – The profile 358 Series has been designed for rapid installation with factory fitted threaded Inserts to all Posts for Security Fixing Brackets and Posts set at 2.53m centres ensures that on site time and disruption is kept to a minimum.

### Applications

Profile 358 – 3D Series is highly recommended for Schools, Public Buildings, Hospitals, Police Stations, Secure areas, Factories, Car parks, Business and Retail Parks.



## Panels

All Panels have a width of 2515mm ranging from 2000 to 3000mm in height. The panels are flush at the Top and Bottom. Mesh apertures are 12.7 x 76.2mm, manufactured from 4.0mm pre galvanised wire to BS EN 10244-2:2009 class D and polyester resin powder coated to give a minimum 10 year life.

## Posts

Standard Posts are manufactured from pre galvanised 60 x 60 x 2mm or 60 x 80 x 2mm or 60 x 40 x 2mm Rolled Hollow Section. Posts are factory fitted with Hexagonal threaded Inserts providing a clean and flush rear face free from hazardous bolts and nut protrusions, and are supplied complete with top cap; again all posts are polyester resin powder coated to give a minimum 10 year life.

## Fixings

Specially designed metal fixing brackets are supplied complete with stainless steel M8 bolts. Where stepping is required for sloping sites additional brackets and Tech bolt kits are provided for installation on site.

## Gates

A complete range of Swing Gates and Sliding Gates are available to suit all requirements.

