

# Declaration of Performance

G067

1. Unique identification code of the product type:

**Geocel LMN (Brown 400ml sausage)**

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Sealant intended for Non-structural Glazing applications EN15651-2**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Sherwin-Williams Diversified Brands Ltd  
Thornccliffe Park  
Chapelton  
Sheffield  
S35 2YP**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not Applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 3**

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The Notified Body SKZ – TeConA GmbH (1213) performed Initial Type Testing according to EN 15651-2 and reaction to fire system 3 and issued a test report**

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not Applicable**

7. Declared performance

Essential Characteristic	Declared Performance	Test Standard	Harmonised Standard
Reaction to Fire	Class E	EN 13501-1 and the relevant test standards given therein	EN 15651-2
Release of Chemicals Dangerous to the Environment and Health	None	See product MSDS	
<b>Water Tightness and Air Tightness</b>			
Vertical flow resistance	≤3mm	Modified EN ISO 7390	
Loss of Volume	≤10%	EN ISO 10563	
Adhesion/cohesion properties after exposure to heat water and artificial light	Pass	EN ISO 11431	
Elastic recovery	≥70%	EN ISO 7389	
Durability	Pass	EN ISO 8340 (without ageing) EN ISO 10590 (with ageing)	
Conditioning: Method B Test Substrate: Glass (Unprimed), Aluminium (Unprimed), Mortar M2 (Unprimed), Mortar M1 (with Primer P)			

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer by:



Stuart Oakey  
Technical Manager

Plymouth (UK), April 2014