

MultiTrack NW 18

MultiTrack NW 18 Nonwoven Geotextile, 3000N, 215g/m² - 5.25m x 100m roll



CHARACTERISTIC	VALUE
Description	MultiTrack NW 18 Nonwoven Geotextile, 3000N, 215g/m ² - 5.25m x 100m roll

SPECIFICATION

GENERAL INFORMATION

Stock code	GTNW/18
Range	MultiTrack
Third party certified	CE UKCA
Roll sizes	5.25m x 100m

GEOTEXTILE PROPERTIES

Tensile strength (MD)	EN ISO 10319	18kN/m
Tensile strength (CMD)	EN ISO 10319	18kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	16.5mm
CBR puncture resistance	EN ISO 12236	3000N
Dynamic cone drop	EN ISO 13433	16.5mm
Water permeability	EN ISO 11058	70L/m ² .s
Characteristic opening size	EN ISO 12956	85µm
Thickness under 2kPa	EN ISO 9863-1	1.4mm
Weight	EN ISO 9864	215g/m ²

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the [knowledge base](#).
- All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).
- Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.