

Tarasafe™ Standard

Tarasafe™ Standard is a slip resistant vinyl floor covering with a pure PVC wear layer and deeply inlaid mineral crystal particles (patent pending) It is reinforced with a glass fibre grid in sheet form.

It is treated with Sanasol® antibacterial and fungicidal additives. The product conforms to BS EN 649. It is an ideal solution for heavy traffic applications where enhanced slip resistance, durability, hygiene and easy maintenance is required.

Tarasafe™ Standard is suitable for all heavy traffic and public areas and comes with a 12 year Warranty. 100% recyclable when the product is at the end of its life.

Installation should be carried out in accordance with BS8203-2001, Subfloor to be smooth, hard, and clean and dry prior to laying, where applicable the subfloor must incorporate a Damp Proof Membrane. Gerflor Ltd recommends the use of Gerfix E120 Adhesive. All seams must be hot welded using Gerflor matching weld rod.

Consult with Gerflor Ltd for technical details and to obtain samples.

Flooring: Slip resistant heavy duty PVC

Manufacturer and reference: Gerflor Ltd, Wedgnock House, Wedgnock Lane, Warwick, CV34 5AP. Tel: 01926 622600, Fax: 01926 401647

Email: contractuk@gerflor.com

Reference: Tarasafe™ Standard

BS EN 685: Class 34 / 43

EN 660.2: Wear Resistance $\leq 2.0 \text{ mm}^3$

Width: 2000 mm

Thickness: 2.0 mm

Adhesive (and primer if recommended by manufacturer): Gerfix E120 Adhesive

Seam welding: All seams must be hot welded using Gerflor matching weld rod

Maintenance: Tarasafe™ Standard has a high PVC content and contains deeply inlaid mineral crystals as the slip resistant medium. Emulsion Dressings should not be applied. The product has a **Low Maintenance Classification**

Post Installation Maintenance: Sweep/Vacuum, Damp Mopping with Neutral Detergent

Regular Maintenance: Sweep/Vacuum, Damp Mopping with Neutral Detergent

Periodic Maintenance:

1. Spray Cleaning using a Rotary Polishing Machine with a Medium Pad and/or Bristle Brush