

O35 LED

Decorative LED bollard in different heights



Glamox O35 is a decorative LED bollard. Suitable for lighting pathways, entrances, parks and amenity areas. O35 is available in different heights for different applications. The "Mini bollard" can also be used as a wall fixture. Available in three different colours; black, aluminium grey or anthracite. The bollard has 360° radial light distribution.

O35 is manufactured with luminaire housing in extruded and die-cast aluminium. Phosphor-chromated for extra protection followed by a first layer of epoxy powder and a second layer of polyester powder coated paint finish. Supplied with clear polycarbonate diffuser. The bollard has silicone gasket and all screws are in stainless steel.

O35 LED

TECHNICAL DESCRIPTION

LIGHT SOURCE

LED 1200 840

BALLAST

Fixed output (HF).

BODY MATERIAL & COLOUR

Housing in extruded and die-cast aluminium. Phosphor-chromated for extra protection followed by a first layer of epoxy powder and a second layer of polyester powder coated paint finish. Black, aluminium grey or anthracite. Clear polycarbonate diffuser. Silicone gasket. Stainless steel screws.

MOUNTING

Mounted to a root column that has to be ordered separately or directly to fixed base.

ACCESSORIES

Root column.

CONNECTION

Supplied with IP68 connector and pre-assembled 2x0,75 mm² cable.

LOAD AND FUSES

Maximum quantities of drivers on MCB 16A Type B: 60 pcs, 16A Type C: 120 pcs.

MEASUREMENT DRAWINGS

