

Lafite Connect

Product information:

Lafite Connect features a range of complementary designs that can work together to create interesting and contemporary floor schemes. Lafite Connect is suitable for a wide range of environments including commercial, education and healthcare.



Warranties:

10 year wear warranty
 10 year anti-static warranty
 Full warranty details available on request



Environmental Profiles
 ENP 399dx, 399dy & 399dz

BRE Global (BREEAM):

'A+' Education (tile)
 'A+' Healthcare (tile)
 'A+' Retail replacement by fashion (tile)

Specification:

Product Form	Tile
Product Dimensions	500mm x 500mm
Product Construction	Tufted Loop Pile
Surface Yarn	100% Aquafil Solution Dyed Nylon
Total Carpet Weight	4415 g/m ²
Tufted Pile Weight	540 g/m ²
Gauge	39.4 per dm
Stitches	43.3 per dm
Primary Backing	Non-woven
Secondary Backing	Bitumen
Total Carpet Thickness	6.8mm

Performance Specification

Classification BSEN 1307	Wear Class 33
Castor Chair BSEN 985 Test A	Pass
Static Electricity ISO 6356	<2kV

Flammability


BSEN 13501-1	Class Bfl-s1
--------------------	--------------

For recommended adhesives contact Technical Services on 01625 428922.

Lafite Connect




Broadloom



Quarter Turn

Lafite Stripes & Lafite Design



Must be laid Quarter Turn

AQUAFIL
 synthetic fibres and polymers



ISO 9001 : FM 10763
 ISO 14001 : EMS 59511



BS OHSAS 18001
 IV 18/18493

16237

GRADUS

Gradus Carpets Park Green Macclesfield Cheshire SK11 7LZ England UK Tel: 01625 859000 Fax: 01625 850352

For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780

www.gradusworld.com