




## iMod® Recessed

LED

22W	LED	IM248	LED	22	I	357
28W	LED	IM248	LED	28	I	357



230V  
50Hz
 
 20
 
 580 x 580mm
 
 6.5 kg


Designed for plasterboard type ceilings

	CRI 80	22W	28W
<b>3 Warm White LED (3000K)</b>			
Lumen Output		3381 lm	4011 lm
LOR		0.91	0.91
CRI		80	80
Total Power		23.6W	29.6W
Power Factor		0.98	0.98
Running Current		0.10A	0.13A
Inrush Current		32.0A (240us)	32.0A (240us)
Efficacy		130 lm/W	123 lm/W
Emergency Output (BLF)		405 lm (12%)	401 lm (10%)
<b>4 Neutral White LED (4000K)</b>			
Lumen Output		3752 lm	4380 lm
LOR		0.91	0.91
CRI		80	80
Total Power		23.6W	29.6W
Power Factor		0.98	0.98
Running Current		0.10A	0.13A
Inrush Current		32.0A (240us)	32.0A (240us)
Efficacy		144 lm/W	134 lm/W
Emergency Output (BLF)		450 lm (12%)	438 lm (10%)

### LG7 in accordance with SLL Code for Lighting 2012\*

- Zhaga Book 7 LED
- Available in a choice of lumen outputs, delivering up to 4380 lumens
- Efficacies up to 144 lm/W
- Outstanding performance with an LOR of 0.91
- Luminance limits below 3000cd/m<sup>2</sup> at the 65° cut off \*
- Life expectancy in excess of 55,000 hours (L80 B10)
- 3000K and 4000K versions available
- Colour stability within 3 MacAdams
- TP(b) rated as standard with TP(a) available on request

### Photometrics



351 DLOR: 0.91

#### Gear types F & G must be operated through a DSI

- A** Integral Driver
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency

■ 3 Warm (3000K)
 ■ 4 Neutral (4000K)

■ I White (RAL 9010)

Interconnection options available contact Sales