

## Opulus Pendant



### Fluorescent

40W	TFL	2GX13	PN998	-	TFL040	-	+	171
55W	TFL	2GX13	PN998	-	TFL055	-	+	171

### Fluorescent & PIR

40W	TFL	2GX13	PN999	-	TFL040	-	+	171
55W	TFL	2GX13	PN999	-	TFL055	-	+	171

PIR versions only suitable for use with Gear Types F and G

- Opulus features a large diameter clear outer Halo Glass, combined with lightly etched inner Halo
- High output T5 fluorescent light source with an impressive 16,000 hour lamp life
- Luminaire offers excellent lighting performance
- Suspended and Surface versions incorporate a wide choice of integral Gear Types
- Vivid Luminescent Halo options enable creativity with colour
- Optional in-built Passive Infra-Red Detector can significantly improve energy efficiency
- Supplied with single point 3x 2m Suspension Wire as standard
- Complementary Opulus Recessed Downlighters and Surface versions are available



### Gear types F & G must be operated through a DSI

- D** High Frequency
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency

**1** White (RAL 9010)   **2** Urban Graphite (RAL 7046)   **3** Black (RAL 9005)

### Luminescent Halo Options *Shown*

**353** 3x 5m Suspensions (wires only)


Tel: (0191) 280 9911   Email: [technical@hacel.co.uk](mailto:technical@hacel.co.uk)   Web: [www.hacel.co.uk](http://www.hacel.co.uk)

**Hacel**<sup>®</sup>  
Fluent in Lighting



## Opulus Pendant

### Photometrics



**171** ULOR: 0.02 DLOR: 0.70

### Options


#### ■ Luminescent Halo Options



**326** Neptune Blue



**327** Mars Red



**329** Acid Green