




Opulus Surface

		☀		🕒		👁		📺		🗣		+		⚠	
Fluorescent															
40W	TFL	2GX13	SD941	—	TFL040	—	+	—	—	—	—	+	—	—	171
55W	TFL	2GX13	SD941	—	TFL055	—	+	—	—	—	—	+	—	—	171
Fluorescent & PIR															
40W	TFL	2GX13	SD991	—	TFL040	—	+	—	—	—	—	+	—	—	171
55W	TFL	2GX13	SD991	—	TFL055	—	+	—	—	—	—	+	—	—	171



230V
50Hz

IP
20

⌀
50mm

⚖
6.0 kg

PIR versions only suitable for use with Gear Types F and G only

- Opulus features a large diameter clear outer Halo Glass, combined with lightly etched inner Halo
- High output T5 fluorescent light source with an impressive 16,000 hour lamp life
- Luminaire offers excellent lighting performance
- Vivid Luminescent Halo options enable creativity with colour
- Optional in-built Passive Infra-Red Detector can significantly improve energy efficiency
- Complementary Opulus Recessed Downlighters and Pendant are available

Luminescent Halo Options




326 Neptune Blue

327 Mars Red

329 Acid Green

Photometrics



171 ULOR: 0.02 DLOR: 0.70

Gear types F & G must be operated through a DSI

- D** High Frequency
 - E** Emergency
 - F** Digital Dim
 - G** Digital Dim + Emergency
 - J** Switch Dim (WL286 only)
 - K** K Switch Dim + Emergency (WL286 only)
 - S** DALI Dim
 - T** DALI Dim + Emergency
- 1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)
- Luminescent Halo Options *Shown*

Tel: (0191) 280 9911 Email: technical@hacel.co.uk Web: www.hacel.co.uk