

Opulus with PIR *Shown*
Luminaires with an inbuilt PIR Detector provide control to improve energy efficiency.

Opulus



Fluorescent


| | | | | | |
|-----|-----|-------|-------|--------|-----|
| 40W | TFL | 2GX13 | ID984 | TFL040 | 176 |
| 55W | TFL | 2GX13 | ID984 | TFL055 | 176 |

Fluorescent & PIR

| | | | | | |
|-----|-----|-------|-------|--------|-----|
| 40W | TFL | 2GX13 | ID985 | TFL040 | 176 |
| 55W | TFL | 2GX13 | ID985 | TFL055 | 176 |

PIR versions only suitable for use with Gear Types F, G

- Subtly etched glass fascia providing excellent ambient lighting
- Slim recessing depth of only 42mm
- Wide choice of high frequency gear types and PIR control
- High quality reflector offers superb performance
- Reliable T5 Fluorescent circular light source
- Complementary Pendant and Surface luminaires are available.




230V
50Hz

IP
20

405mm Ø

3.8 kg

Photometrics



176 DLOR: 0.75

Gear types F & G must be operated through a DSI

- D** High Frequency
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency

1 White (RAL 9010) **2** Urban Graphite (RAL 7046) **3** Black (RAL 9005)

Tel: (0191) 280 9911 Email: technical@hacel.co.uk Web: www.hacel.co.uk

Hacel[®]
Fluent in Lighting