


230V
50Hz IP 20 50mm 2.0 kg

	CRI 80	8W	12W	17W
3 Warm White LED (3000K)				
Lumen Output		1085 lm	1540 lm	2100 lm
LOR		0.87	0.87	0.87
CRI		80	80	80
Total Power		9.1W	13.1W	18.2W
Power Factor		0.90	0.95	0.93
Running Current		0.04A	0.06A	0.09A
Inrush Current		8.0A (80us)	15.0A (204us)	8.0A (80us)
Efficacy		103 lm/W	102 lm/W	100 lm/W
Emergency Output (BLF)		N/A	N/A	N/A
4 Neutral White LED (4000K)				
Lumen Output		1150 lm	1630 lm	2229 lm
LOR		0.87	0.87	0.87
CRI		80	80	80
Total Power		9.1W	13.1W	18.2W
Power Factor		0.90	0.95	0.93
Running Current		0.04A	0.06A	0.09A
Inrush Current		8.0A (80us)	15.0A (204us)	8.0A (80us)
Efficacy		109 lm/W	108 lm/W	106 lm/W
Emergency Output (BLF)		N/A	N/A	N/A

Photometrics



424 DLOR: 0.87

Sequa Eco



LED

8W	LED	PN982	LED	08	I	+	424
12W	LED	PN982	LED	12	I	+	424
17W	LED	PN982	LED	17	I	+	424

- Sequa Eco features a stylish subtly ribbed opal acrylic refractor
- Available in a choice of lumen outputs, delivering up to 2229 lumens
- Efficacies up to 109 lm/W
- Life expectancy in excess of 50,000 hours (L80 B10)
- Glare free balanced illumination
- 2m Suspension Wire with chrome clutch adjustment supplied as standard
- Colour stability with 3 MacAdams
- Colour options apply to ceiling plate

Gear types F & G must be operated through a DSI

- A Integral Driver
- F Digital Dim
- J Switch Dim
- S DALI Dim

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

242 5m Suspension (wire only)

Tel: (0191) 280 9911 Email: technical@hacel.co.uk Web: www.hacel.co.uk

Hacel[®]
Fluent in Lighting