


SkyMod® Linear Grid



LED

21W	LED	IM247	LED	21	442
33W	LED	IM247	LED	33	442
46W	LED	IM247	LED	46	442




	CRI 80	21W	33W	46W
3 Warm White LED (3000K)				
Lumen Output		3542 lm	5192 lm	6780 lm
LOR		0.81	0.81	0.81
CRI		80	80	80
Total Power		24.1W	37.2W	49.9W
Power Factor		0.95	0.95	0.95
Running Current		0.11A	0.17A	0.23A
Inrush Current		15.0A (230us)	21.0A (250us)	28.0A (210us)
Efficacy		119 lm/W	113 lm/W	110 lm/W
Emergency Output (BLF)		425 lm (12%)	415 lm (8%)	406 lm (6%)
4 Neutral White LED (4000K)				
Lumen Output		3780 lm	5540 lm	7236 lm
LOR		0.81	0.81	0.81
CRI		80	80	80
Total Power		24.1W	37.2W	49.9W
Power Factor		0.95	0.95	0.95
Running Current		0.11A	0.17A	0.23A
Inrush Current		15.0A (230us)	21.0A (250us)	28.0A (210us)
Efficacy		127 lm/W	120 lm/W	117 lm/W
Emergency Output (BLF)		453 lm (12%)	443 lm (8%)	434 lm (6%)

LG7 in accordance with SLL Code for Lighting 2012*

- Features an Opal polycarbonate diffuser with wipe clean surface
- Available in a choice of lumen outputs, delivering up to 7236 lumens
- Efficacies up to 127 lm/W
- 21W version has luminance limits below 3000cd/m² at the 65° cut off *
- Life expectancy in excess of 60,000 hours (L80 B10)
- Colour stability within 3 MacAdams
- Wide choice of high quality control gear
- TP(b) rated as standard

Photometrics



Gear types F & G must be operated through a DSI

- A** Integral Driver
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency

3 Warm (3000K) 4 Neutral (4000K)

I White (RAL 9010)

Interconnection options available contact Sales